

Product datasheet

Specifications



Galaxy PW 2nd Gen 100kVA 3:1 UPS 220VAC 12 Pulse 220VDC with input transformer, Startup 5x8

EPWUPS100KU12PTS

Price: 778,320.00 ZAR

Overview

Presentation Transformer-based 100 kVA 3-phase input, single-phase output UPS with 12-pulse SCR technology and a 220 VDC internal DC bus. Ideal for industrial applications, this UPS includes 5x8 start-up service.

Lead time Special Order - Call for Quoted Lead Times

Main

Main Input Voltage 400 V 3 phases

Input voltage 380 V
415 V

Maximum input current 221 A

Max short time withstand current 10 kA

Input voltage limits 400 V

Network frequency 45...55 Hz

Output voltage 400 V 3 phases

Output voltage 380 V
415 V

Rated power in W 80 kW

rated power in VA 100 kVA

Harmonic distortion Less than 2 %

Maximum configurable power in VA 100 kVA

Maximum configurable power in W 80 kW

Output harmonic distortion < 2% linear load and < 4% non-linear load

Output overload operation 10 minutes at 125% and 60 seconds at 150%

Wave type Sine wave

Output frequency 50 Hz +/- 1 %

Complementary

Battery voltage 192...240 V

Max current discharge 578 A

Control panel Touch screen LCD user interface

Colour Light grey

Height 180 cm

Width 160 cm

Depth 80 cm

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Net weight	1239 kg
Redundant	No
Product or component type	Uninterruptible power supply (UPS)

Environment

Product certifications	CE
Standards	IEC 62040-1-1 IEC 62040-2 IEC 62040-3 IEC 62040-4 ISTA 2B
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-25...55 °C
Storage altitude	0...9999.9 m
IP degree of protection	IP31
Relative humidity	0...95 % non-condensing
Storage Relative Humidity	0...95 % non-condensing
Acoustic level	70 dBA
Heat dissipation	11760 Btu/h
Operating altitude	0...3281 ft

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2085 mm
Package 1 Width	928 mm
Package 1 Length	1728 mm
Package 1 Weight	1341 kg

Contractual warranty

Warranty (in months)	12
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint 602 ton CO2 eq.

Environmental Disclosure [Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number 06cb433d-2f38-469a-a05f-575f1433c88c

REACH Regulation [REACH Declaration](#)

Use Longer



Lifetime extension

Repair No

Use Again



Repack and remanufacture

End of life manual availability [End of Life Information](#)

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Product datasheet EPWUPS100KU12PTS

Image of product / Alternate images

Alternative

