

# Product datasheet

Specifications



Circuit breaker, ComPacT  
NS1600H, 70kA at 415VAC, 4P,  
fixed, manually operated,  
MicroLogic 2.0E control unit, 1600A

C160H42EFM

**Price: 73,825.70 ZAR**

## Main

|                                |  |
|--------------------------------|--|
| Range                          | ComPacT  |
| Product name                   | ComPacT NS new generation  |
| Range of product               | ComPacT NS630b...1600 new generation   |
| Product or component type      | Circuit breaker  |
| Device application             | Distribution   |
| Number of poles                | 4P   |
| Protected poles description    | 4D   |
| Neutral position               | Left   |
| [In] rated current             | 1600 A at 50 °C  |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz  |
| Network type                   | AC   |
| Network frequency              | 50/60 Hz   |
| Suitability for isolation      | Yes conforming to EN/IEC 60947-2   |
| Utilisation category           | Category B   |
| Breaking capacity              | 85 kA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2<br>70 kA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2<br>65 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>50 kA Icu at 500/525 V AC 50/60 Hz conforming to IEC 60947-2<br>42 kA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Breaking capacity code         | H 70 kA 415 V AC   |
| Trip unit name                 | MicroLogic 2.0 E   |
| Trip unit technology           | Electronic   |
| Trip unit protection functions | LI   |
| Control type                   | Manually operated  |
| Mounting mode                  | Fixed  |

## Complementary

|  |  |
|--|--|
| [Ui] rated insulation voltage            | 800 V AC 50/60 Hz conforming to IEC 60947-2  |
| [Uimp] rated impulse withstand voltage   | 8 kV conforming to IEC 60947-2   |
| [Ics] rated service breaking capacity    | 37 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2<br>37 kA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2<br>37 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>30 kA at 500/525 V AC 50/60 Hz conforming to IEC 60947-2<br>22 kA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Icw] rated short-time withstand current | 19.2 kA 1 s conforming to IEC 60947-2  |

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

|  |  |
|--|--|
| <b>Mechanical durability</b>                                     | 10000 cycles   |
| <b>Electrical durability</b>                                     | 1000 cycles at 690 V In<br>2000 cycles at 690 V In/2<br>2000 cycles at 440 V In<br>5000 cycles at 440 V In/2 |
| <b>Power losses</b>  | 74 W   |
| <b>Mounting support</b>  | Backplate  |
| <b>Upside connection</b>   | Front  |
| <b>Downside connection</b>                                       | Front  |
| <b>Connection pitch</b>  | 70 mm  |
| <b>Protection type</b>   | L : for overload protection (long time)<br>I : for instantaneous short-circuit protection                    |
| <b>Trip unit rating</b>  | 1600 A at 50 °C  |
| <b>Long-time pick-up adjustment type Ir (thermal protection)</b> | Adjustable 9 settings  |
| <b>[Ir] long-time protection pick-up adjustment range</b>        | 0.4...1 x In   |
| <b>Long-time protection delay adjustment type tr</b>             | Adjustable 9 settings  |
| <b>[tr] long-time delay adjustment range</b>                     | 12.5...600 s at 1.5 x Ir<br>0.5...24 s at 6 x Ir<br>0.7...16.6 s at 7.2 x Ir                                 |
| <b>Thermal memory</b>  | 20 mn  |
| <b>Instantaneous protection pick-up adjustment type Ii</b>       | Adjustable   |
| <b>[Ii] instantaneous protection pick-up adjustment range</b>    | 1.5...10 x Ir  |
| <b>Earth-leakage protection</b>                                  | Without  |
| <b>Neutral protection setting</b>                                | No protection (3D)<br>0.5 x Ir (3D + N/2)<br>1 x Ir (4D)   |
| <b>Zone selective interlocking ZSI</b>                           | Without  |
| <b>Auxiliary contact composition</b>                             | 1 NO/NC  |
| <b>Local signalling</b>  | 4 LEDs (red) for fault indication<br>1 LED (yellow) for overload   |
| <b>Display type</b>  | LCD display  |
| <b>Type of measurement</b>                                       | Energy meter   |
| <b>Width (W)</b>   | 280 mm   |
| <b>Height (H)</b>  | 327 mm   |
| <b>Depth (D)</b>   | 147 mm   |
| <b>Net weight</b>  | 18 kg  |

## Environment

|  |                              |
|--|------------------------------|
| <b>Standards</b>                         | EN/IEC 60947-2               |
| <b>Product certifications</b>            | IECEE CB Scheme              |
| <b>Overvoltage category</b>              | III                          |
| <b>Electrical shock protection class</b> | Class II on front face       |
| <b>Pollution degree</b>                  | 3 conforming to IEC 60947    |
| <b>IP degree of protection</b>           | IP40 conforming to IEC 60529 |

|  |  |
|--|--|
| <b>IK degree of protection</b>               | IK07 conforming to EN 50102                                  |
| <b>Ambient air temperature for operation</b> | -25...70 °C  |
| <b>Ambient air temperature for storage</b>   | -40...85 °C  |
| <b>Relative humidity</b>                     | 0...95 %   |
| <b>Operating altitude</b>                    | 0...2000 m without derating<br>2000 m...5000 m with derating |

## Packing Units

|                                     |           |
|-------------------------------------|-----------|
| <b>Unit Type of Package 1</b>       | PCE       |
| <b>Number of Units in Package 1</b> | 1         |
| <b>Package 1 Height</b>             | 37.000 cm |
| <b>Package 1 Width</b>              | 38.000 cm |
| <b>Package 1 Length</b>             | 30.000 cm |
| <b>Package 1 Weight</b>             | 17.035 kg |

## Contractual warranty

|                             |    |
|-----------------------------|----|
| <b>Warranty (in months)</b> | 18 |
|-----------------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Total lifecycle Carbon footprint 1621

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number 76c2e213-3b51-4d8b-afdf-632ded42d731

REACH Regulation [REACH Declaration](#)

Halogen-free status Product contains halogen above thresholds

PVC free No

Silicone-free No

## Use Longer

### Lifetime extension

Repair No

## Use Again

### Repack and remanufacture

End of life manual availability [End of Life Information](#)

Removable battery User replaceable

Take-back No

WEEE Label The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Technical Illustration

Assembly's dimensions

---

