

# Product datasheet

Specifications



## iEM3310 energy meter - 125 A - 1 pulse O - MID

A9MEM3310

**Price: 5,840.51 ZAR**

### Main

Range	Acti9
range of product	Acti9 iEM3000
Product or component type	Energy meter
Device short name	iEM3310

Market segment	Buildings small building cost management: billing: main incomer Buildings small building cost management: billing: sub feeder Buildings small building cost management: billing: panelboard Buildings medium building cost management: billing: main incomer Buildings medium building cost management: billing: sub feeder Buildings medium building cost management: billing: panelboard Buildings large building cost management: billing: main incomer Buildings large building cost management: billing: sub feeder Buildings large building cost management: billing: panelboard Buildings multi-site cost management: billing: main incomer Buildings multi-site cost management: billing: sub feeder Buildings multi-site cost management: billing: panelboard Data center cost management: billing Healthcare cost management: billing Industry cost management: billing Buildings small building cost management: cost allocation: main incomer Buildings small building cost management: cost allocation: sub feeder Buildings small building cost management: cost allocation: panelboard Buildings medium building cost management: cost allocation: main incomer Buildings medium building cost management: cost allocation: sub feeder Buildings medium building cost management: cost allocation: panelboard Buildings large building cost management: cost allocation: main incomer Buildings large building cost management: cost allocation: sub feeder Buildings large building cost management: cost allocation: panelboard Buildings multi-site cost management: cost allocation: main incomer Buildings multi-site cost management: cost allocation: sub feeder Buildings multi-site cost management: cost allocation: panelboard Data center cost management: cost allocation Healthcare cost management: cost allocation Industry cost management: cost allocation
----------------	--

### Complementary

Poles description	3P 1P + N 3P + N
Type of measurement	Active energy
Device application	Sub billing Partial meter
Accuracy class	Class 1 active energy conforming to IEC 62053-21 Class 1 active energy conforming to IEC 61557-12 Class B active energy conforming to EN 50470-3
input type	Direct connection
[In] rated current	125 A
Rated voltage	100...277 V 173...480 V

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

<b>Network frequency</b>	60 Hz 50 Hz
<b>Technology type</b>	Electronic
<b>Display type</b>	LCD display
<b>Sampling rate</b>	32 samples/cycle
<b>Measurement current</b>	0...125 A
<b>Maximum value measured</b>	99999999.9 kWh
<b>Communication port protocol</b>	-
<b>Communication port support</b>	-
<b>Local signalling</b>	Green indicator light: power ON Yellow flashing LED: accuracy checking
<b>Number of inputs</b>	0
<b>Number of outputs</b>	1 pulse
<b>Mounting mode</b>	Clip-on
<b>Mounting support</b>	DIN rail
<b>Connections - terminals</b>	Screw terminals 50 mm <sup>2</sup> cable(s)
<b>Overvoltage category</b>	III
<b>Standards</b>	BS EN 61557-12:2021 IEC 61557-12:2021 EN 61557-12:2021 BS EN 61326-1 IEC 61326-1 EN 61326-1 BS EN 62052-11:2020 IEC 62052-11:2020 EN 62052-11:2020 BS EN 62053-21 IEC 62053-21 EN 62053-21 BS EN 62052-23 IEC 62053-23:2020 EN 62052-23 BS EN 62052-31:2015 IEC 62052-31:2015 EN 62052-31:2015 BS EN 61010-1:2010 EN 61010-1:2010 IEC 61010-1:2010 UL 61010-1:2010 BS EN 61010-2-30 IEC 61010-2-30 EN 61010-2-30 UL 61010-2-30 BS EN 50470-3 EN 50470-3 BS EN 50470-1 EN 50470-1 ANSI C12.16
<b>Product certifications</b>	CE conforming to IEC 61010-1 (safety) CE conforming to EN 61557-12 (power monitor) CE conforming to EN/IEC 61326-1 (EMC) UKCA conforming to BS EN 61010-1 (safety) UKCA conforming to BS EN 61557-12 (power monitor) UKCA conforming to BS EN 61326-1 (EMC) CULus conforming to UL 61010-1 (safety) CULus conforming to EN 61010-1 (safety) EAC conforming to EN 50470-3 (sub-meter) RCM conforming to EN 62052 (sub-meter) KZ conforming to EN 50470-3 (sub-meter) METAS conforming to EN 50470-1 (sub-meter) MID conforming to EN 50470-3 (sub-meter) MID conforming to EN 50470-1 (sub-meter) NMI conforming to NMI M 6-1

---

Compatibility code	IEM3310
--------------------	---------

## Environment

---

IP degree of protection	IP40 front panel: conforming to IEC 60529 IP20 body: conforming to IEC 60529
-------------------------	---

---

Pollution degree	2
------------------	---

---

Relative humidity	5...95 % at 50 °C
-------------------	-------------------

---

Ambient air temperature for operation	-25...55 °C - MID -25...70 °C - IEC -25...60 °C - IEC
---------------------------------------	---

---

Ambient air temperature for storage	-40...85 °C
-------------------------------------	-------------

---

Operating altitude	< 3000 m
--------------------	----------

---

Colour	White
--------	-------

---

9 mm pitches	14
--------------	----

---

Width	126 mm
-------	--------

---

Height	103.2 mm
--------	----------

---

Depth	69.3 mm
-------	---------

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Number of Units in Package 1	1
------------------------------	---

---

Package 1 Height	8.700 cm
------------------	----------

---

Package 1 Width	11.300 cm
-----------------	-----------

---

Package 1 Length	13.100 cm
------------------	-----------

---

Package 1 Weight	674.000 g
------------------	-----------

---

Unit Type of Package 2	S03
------------------------	-----

---

Number of Units in Package 2	16
------------------------------	----

---

Package 2 Height	30.000 cm
------------------	-----------

---

Package 2 Width	30.000 cm
-----------------	-----------

---

Package 2 Length	40.000 cm
------------------	-----------

---

Package 2 Weight	11.100 kg
------------------	-----------

---

Unit Type of Package 3	P12
------------------------	-----

---

Number of Units in Package 3	384
------------------------------	-----

---

Package 3 Height	110.000 cm
------------------	------------

---

Package 3 Width	80.000 cm
-----------------	-----------

---

Package 3 Length	120.000 cm
------------------	------------

---

Package 3 Weight	275.400 kg
------------------	------------

## Contractual warranty

---

Warranty (in months)	18
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint 60

Environmental Disclosure [Product Environmental Profile](#)

## Use Better



### Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number 1370256b-4f45-45cb-ba74-d245fc174cf9

REACH Regulation [REACH Declaration](#)

## Use Longer



### Lifetime extension

Repair No

## Use Again



### Repack and remanufacture

End of life manual availability [End of Life Information](#)

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Technical Illustration

User interface / product ON

---

