

# Product datasheet

Specifications



## iEM3555 energy meter - Modbus - 1 DI - 1 DO - multi-tariff - Rogowski coil

A9MEM3555

**Price: 9,646.18 ZAR**

### Main

Range	Acti9
range of product	Acti9 iEM3000
Product or component type	Energy meter
Device short name	iEM3555

Market segment	Buildings small building cost management: billing: main incomer Buildings small building cost management: billing: sub feeder Buildings small building cost management: billing: panelboard Buildings medium building cost management: billing: main incomer Buildings medium building cost management: billing: sub feeder Buildings medium building cost management: billing: panelboard Buildings large building cost management: billing: main incomer Buildings large building cost management: billing: sub feeder Buildings large building cost management: billing: panelboard Buildings multi-site cost management: billing: main incomer Buildings multi-site cost management: billing: sub feeder Buildings multi-site cost management: billing: panelboard Data center cost management: billing Healthcare cost management: billing Industry cost management: billing Buildings small building cost management: cost allocation: main incomer Buildings small building cost management: cost allocation: sub feeder Buildings small building cost management: cost allocation: panelboard Buildings medium building cost management: cost allocation: main incomer Buildings medium building cost management: cost allocation: sub feeder Buildings medium building cost management: cost allocation: panelboard Buildings large building cost management: cost allocation: main incomer Buildings large building cost management: cost allocation: sub feeder Buildings large building cost management: cost allocation: panelboard Buildings multi-site cost management: cost allocation: main incomer Buildings multi-site cost management: cost allocation: sub feeder Buildings multi-site cost management: cost allocation: panelboard Data center cost management: cost allocation Healthcare cost management: cost allocation Industry cost management: cost allocation
----------------	--

### Complementary

Poles description	3P 3P + N 1P + N
Type of measurement	Active and reactive energy Active and reactive power Current Voltage
Metering type	Active, reactive, apparent energy (signed, four quadrant)
Device application	Multi-tariff Partial meter Sub billing
Accuracy class	Class 0.5S active energy conforming to IEC 62053-22 Class 0.5S active energy conforming to ANSI C12.20
input type	Rogowski coil 50...5000 A

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

<b>Rated voltage</b>	100...277 V +/- 20 % 173...480 V +/- 20 %
<b>Network frequency</b>	50 Hz 60 Hz
<b>Technology type</b>	Electronic
<b>Display type</b>	LCD display
<b>Sampling rate</b>	32 samples/cycle
<b>Measurement current</b>	50...5000 A
<b>Maximum value measured</b>	99999999.9 kWh 99999999 MWh
<b>tariff input</b>	Tariff (4)
<b>Communication port protocol</b>	Modbus RTU at 9.6, 19.2 and 38.4 kbauds even/odd or none
<b>Communication port support</b>	Screw terminal block: RS485
<b>Local signalling</b>	Green indicator light: power ON Yellow flashing LED: accuracy checking alarm: overload Yellow indicator light: communications are active on the Modbus port (Modbus)
<b>Number of inputs</b>	1 digital 0...5 V/11...40 V 24 V DC
<b>Number of outputs</b>	1 digital (static)
<b>Output voltage</b>	5...40 V DC@50 mA
<b>Mounting mode</b>	Clip-on
<b>Mounting support</b>	DIN rail
<b>Connections - terminals</b>	Current circuit: screw terminals 6 mm <sup>2</sup> cable(s) Voltage circuit: screw terminals 2.5 mm <sup>2</sup> cable(s) Input/output circuit: screw terminals 1.5 mm <sup>2</sup> cable(s) Communication: screw terminals 2.5 mm <sup>2</sup> cable(s)
<b>Tightening torque</b>	Input/output circuit: 0.5 N.m Philips screwdriver Voltage circuit: 0.5 N.m Philips screwdriver Current circuit: 0.8 N.m pozidriv screwdriver Communication: 0.5 N.m Philips screwdriver
<b>Wire stripping length</b>	Input/output circuit: 6 mm Voltage circuit: 8 mm Current circuit: 8 mm Communication: 7 mm
<b>Standards</b>	BS EN 61326-1 IEC 61326-1 EN 61326-1 BS EN 61010-1:2010 EN 61010-1:2010 IEC 61010-1:2010 UL 61010-1:2010 BS EN 61010-2-30 IEC 61010-2-30 EN 61010-2-30 UL 61010-2-30 ANSI C12.20
<b>Product certifications</b>	CE conforming to IEC 61010-1 (safety) CE conforming to EN 61557-12 (power monitor) CE conforming to EN/IEC 61326-1 (EMC) UKCA conforming to BS EN 61010-1 (safety) UKCA conforming to BS EN 61557-12 (power monitor) UKCA conforming to BS EN 61326-1 (EMC) CULus conforming to UL 61010-1 (safety) CULus conforming to EN 61010-1 (safety) KZ RCM
<b>Compatibility code</b>	IEM3555

## Environment

<b>IP degree of protection</b>	IP40 front panel: conforming to IEC 60529 IP20 body: conforming to IEC 60529
<b>IK degree of protection</b>	IK08
<b>Pollution degree</b>	2
<b>Relative humidity</b>	5...95 % at 36 °C
<b>Ambient air temperature for operation</b>	-25...70 °C - IEC
<b>Ambient air temperature for storage</b>	-40...85 °C
<b>Operating altitude</b>	< 3000 m
<b>Colour</b>	White
<b>9 mm pitches</b>	10
<b>Width</b>	90 mm
<b>Height</b>	87 mm
<b>Depth</b>	69 mm

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	8.700 cm
<b>Package 1 Width</b>	9.600 cm
<b>Package 1 Length</b>	10.600 cm
<b>Package 1 Weight</b>	328.000 g
<b>Unit Type of Package 2</b>	S03
<b>Number of Units in Package 2</b>	30
<b>Package 2 Height</b>	30.000 cm
<b>Package 2 Width</b>	30.000 cm
<b>Package 2 Length</b>	40.000 cm
<b>Package 2 Weight</b>	10.310 kg
<b>Unit Type of Package 3</b>	P06
<b>Number of Units in Package 3</b>	240
<b>Package 3 Height</b>	80.000 cm
<b>Package 3 Width</b>	60.000 cm
<b>Package 3 Length</b>	80.000 cm
<b>Package 3 Weight</b>	100.364 kg

## Contractual warranty

<b>Warranty (in months)</b>	18
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint 69

Environmental Disclosure [Product Environmental Profile](#)

## Use Better



### Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number Eeba4d71-dd5e-4897-8804-de4a2fdb525f

REACH Regulation [REACH Declaration](#)

## Use Longer



### Lifetime extension

Repair No

## Use Again



### Repack and remanufacture

End of life manual availability [End of Life Information](#)

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Technical Illustration

User interface / product ON

---

