

# Product datasheet

Specifications



APC Smart-UPS, Line Interactive, 2200VA, Lithium-ion, Rackmount 2U, 230V, 8x IEC C13 + 1x IEC C19, SmartConnect, w/Network Management Card, AVR, LCD

SMTL2200RMI2UCNC

⚠ To be discontinued

⚠ Discontinued on: 01 Dec 2024

**Price: 57,040.00 ZAR**

## Overview

Lead time Usually in Stock

## Main

Main Input Voltage 230 V AC 1 phase

Input voltage 220 V  
240 V

Input Connection Type IEC 60320 C20

Input protection type Circuit breaker

Input voltage limits 160...286 V

Network frequency 50/60 Hz +/- 3 Hz auto-sensing

Output voltage 230 V AC 1 phase

Output voltage 220 V  
240 V

Rated power in W 1980 W

rated power in VA 2200 VA

Output connection type 8 IEC 60320 C13  
1 IEC 60320 C19

Crest factor 3 : 1

Maximum configurable power in VA 2200 VA

Maximum configurable power in W 1980 W

Transfer time 6 ms typical : 10 ms maximum

UPS type Line interactive

Wave type Sine wave

Output frequency 50/60 Hz +/- 3 Hz sync to mains

## Complementary

Battery type Li-Ion (Lithium-Ion)

Battery graph comments This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several v

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

<b>Extended runtime</b>	0
<b>Battery recharge time</b>	2 h
<b>Number of battery replacement quantity</b>	1
<b>Battery design life</b>	8...10 year(s)
<b>Battery charger power</b>	216 W rated
<b>Battery type</b>	Li-Ion (Lithium-Ion) internal included
<b>Control panel</b>	Multifunction LCD status and control console
<b>Emergency power off</b>	Yes
<b>Free slots</b>	1
<b>Preinstalled device</b>	Network management card 3 with environmental monitoring
<b>Alarm</b>	Alarm when on battery : distinctive low battery alarm
<b>UPS connectivity</b>	Serial port SmartConnect port Pre-installed network management card 3 USB port
<b>Surge energy rate</b>	739 J
<b>Number of rack unit</b>	2U
<b>Colour</b>	Black with silver front bezel
<b>Height</b>	86 mm
<b>Width</b>	432 mm
<b>Depth</b>	683 mm
<b>Net weight</b>	33.3 kg
<b>Mounting preference</b>	Lower
<b>Mounting mode</b>	Rack-mounted
<b>USB compatible</b>	Yes
<b>Mounting mode</b>	Rack-mounted with included kit
<b>Provided equipment</b>	Rack mounting brackets Rack mounting support rails Screw Washer USB cable Ethernet patch cable
<b>Number of power module</b>	0
<b>Additional specification</b>	Cloud-enabled monitoring
<b>Redundant</b>	No
<b>Range of product</b>	Smart-UPS
<b>Product or component type</b>	Uninterruptible power supply (UPS)

## Environment

<b>Product certifications</b>	UK PSTI
<b>Ambient air temperature for operation</b>	0...40 °C
<b>Ambient air temperature for storage</b>	-15...45 °C
<b>Storage altitude</b>	0...7620 m
<b>IP degree of protection</b>	IP20

---

<b>Relative humidity</b>	0...95 % non-condensing
<b>Storage Relative Humidity</b>	0...95 % non-condensing
<b>Acoustic level</b>	55 dB
<b>Operating altitude</b>	0...10000 ft

---

## Packing Units

---

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	45.8 cm
<b>Package 1 Width</b>	60 cm
<b>Package 1 Length</b>	98 cm
<b>Package 1 Weight</b>	41.5 kg

---

## Contractual warranty

---

<b>Warranty (in months)</b>	60
-----------------------------	----

---



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

## Use Better



### Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant with Exemptions

SCIP Number

0637234b-27c7-4e32-ae29-543dd4803a99

REACH Regulation

[REACH Declaration](#)



### Energy efficiency

Energy Efficiency Optimized

Energy efficient product

## Use Longer



### Lifetime extension

Repair

No

## Use Again



### Repack and remanufacture

End of life manual availability

[End of Life Information](#)

Removable battery

User replaceable

Take-back

No

WEEE Label


 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

---

