

Product datasheet

Specifications



Galaxy PW 2nd Gen 10kVA 3:1 UPS 220VAC 12 Pulse 220VDC with input transformer, Start-up 5x8

EPWUPS10KU12PTS

Price: 255,760.00 ZAR

Overview

Presentation Transformer-based 10 kVA 3-phase input, single-phase output UPS with 12-pulse SCR technology and a 220 VDC internal DC bus. Ideal for industrial applications, this UPS includes 5x8 start-up service.

Lead time Special Order - Call for Quoted Lead Times

Main

Main Input Voltage 400 V 3 phases

Input voltage 380 V
400 V
415 V

Maximum input current 25 A

Max short time withstand current 10 kA

Input voltage limits 400 V

Network frequency 45...55 Hz

Output voltage 230 V 3 phases

Output voltage 220/230/240 V

Rated power in W 8 kW

rated power in VA 10 kVA

Harmonic distortion Less than 2 %

Maximum configurable power in VA 10 kVA

Maximum configurable power in W 8 kW

Output harmonic distortion < 2% linear load and < 4% non-linear load

Output overload operation 10 minutes at 125% and 60 seconds at 150%

Wave type Sine wave

Output frequency 50 Hz +/- 1 %

Complementary

Battery voltage 192...240 V

Max current discharge 56 A

Control panel Touch screen LCD user interface

Colour Light grey

Height 180 cm

Width 80 cm

Depth 80 cm

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Net weight	404 kg
Product or component type	Uninterruptible power supply (UPS)

Environment

Product certifications	CE
Standards	IEC62040-3 IEC 62040-2 IEC 62040-4 IEC 62040-1-1 ISTA 2B
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-25...55 °C
Storage altitude	0...10000 m
IP degree of protection	IP31
Relative humidity	0...95 % non-condensing
Storage Relative Humidity	0...95 % non-condensing
Acoustic level	70 dBA
Heat dissipation	4350 Btu/h
Operating altitude	0...1000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2085 mm
Package 1 Width	928 mm
Package 1 Length	928 mm
Package 1 Weight	474 kg

Contractual warranty

Warranty (in months)	12
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint 104 ton CO2 eq.

Environmental Disclosure [Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number 06cb433d-2f38-469a-a05f-575f1433c88c

REACH Regulation [REACH Declaration](#)

Use Longer



Lifetime extension

Repair No

Use Again



Repack and remanufacture

End of life manual availability [End of Life Information](#)

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins