

# Product datasheet

Specifications



## APC Smart-UPS On-Line, 2200VA, Rackmount 2U, 230V, 6x C13+2x C19 IEC outlets, Network Card, W/ rail kit, W/O Lithium-ion external battery

SRT2200UXI-NCLI

### Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead time	Usually in Stock

### Main

Main Input Voltage	230 V AC 1 phase
Input Connection Type	BS1363A British IEC 60320 C20 Schuko CEE 7 / EU1-16P
Input voltage limits	50...150 V 40% load 80...150 V
Network frequency	40...70 Hz auto-sensing
Output voltage	230 V 1 phase
Rated power in W	1980 W
rated power in VA	2200 VA
Output connection type	6 IEC 60320 C13 2 IEC 60320 C19
Bypass type	Built-in bypass
Crest factor	3 : 1
Harmonic distortion	Less than 2 %
Maximum configurable power in VA	2200 VA
Maximum configurable power in W	1980 W
UPS type	Double conversion online
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

### Complementary

Battery type	Li-Ion (Lithium-Ion)
Extended runtime	1
Number of battery filled slots	0
Number of battery free slots	0
Battery type	Li-Ion (Lithium-Ion) internal included
Emergency power off	Yes
Free slots	0

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

<b>Preinstalled device</b>	Network management card 3 with environmental monitoring
<b>Alarm</b>	Audible and visible alarms : prioritized by severity
<b>UPS connectivity</b>	Serial port USB port Pre-installed network management card 3
<b>Surge energy rate</b>	432 J
<b>Number of rack unit</b>	2U
<b>Cable length</b>	1.8 m
<b>Number of cables</b>	1
<b>Colour</b>	Black
<b>Height</b>	432 mm
<b>Width</b>	85 mm
<b>Depth</b>	508 mm
<b>Net weight</b>	22 kg
<b>Mounting preference</b>	No preference
<b>Mounting mode</b>	Rack-mounted with kit
<b>Two post mountable</b>	0
<b>USB compatible</b>	Yes
<b>Mounting position</b>	Vertical
<b>Mounting mode</b>	Rack-mounted with included kit
<b>Provided equipment</b>	CD with software Communication cable Documentation CD Installation guide Removable support feet USB cable Warranty card
<b>Number of power module filled slots</b>	0
<b>Number of power module free slots</b>	0
<b>Additional specification</b>	High density
<b>Redundant</b>	No
<b>Range of product</b>	Smart-UPS On-Line
<b>Product or component type</b>	Uninterruptible power supply (UPS)
<b>Number of tare power</b>	15 W
<b>Curve equation</b>	Efficiency
<b>Curve load maximum</b>	100 %
<b>Curve X-axis maximum</b>	100 %
<b>Curve X-axis minimum</b>	0 %
<b>Curve X-axis title</b>	Load
<b>Curve X-axis units</b>	Percentage
<b>Curve Y-axis maximum</b>	100 %
<b>Curve Y-axis minimum</b>	50 %
<b>Curve Y-axis title</b>	Efficiency
<b>Curve Y-axis units</b>	Percentage

Graph display	1
Show note OP temperature	No
Battery curve	D
Liquid value	0
UPS design life	7 year(s)
Battery power in VAH	0 VAh runtime
UPS size	S

## Environment

Product certifications	CE EAC UK PSTI
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-20...50 °C
Storage altitude	0...15240 m
IP degree of protection	IP20
Relative humidity	0...95 % non-condensing
Storage Relative Humidity	0...95 % non-condensing
Acoustic level	50 dBA
Heat dissipation	317 Btu/h
Operating altitude	0...10000 ft

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.6 cm
Package 1 Width	74.9 cm
Package 1 Length	59.4 cm
Package 1 Weight	29.6 kg

## Contractual warranty

Warranty (in months)	60
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint 8525

## Use Better



### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number A64c500c-f72a-458b-8faa-8175a94429fe

REACH Regulation [REACH Declaration](#)

## Use Longer



### Lifetime extension

Repair No

## Use Again



### Repack and remanufacture

End of life manual availability [End of Life Information](#)

Removable battery User replaceable

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins