

Product datasheet

Specifications



modular single phase power meter iEM2055 - 230V - 45A with communication Modbus - MID

A9MEM2055

⚠ Discontinued on: 01 Dec 2024

⚠ To be discontinued

Main

Range	Acti9
family	Acti9 iEM2000
Product or component type	Energy meter
Device short name	iEM2055

Complementary

Poles description	1P + N
Type of measurement	Active energy Active and reactive power Power factor Current Voltage Frequency Apparent power
Metering type	Active energy (signed, two quadrant)
Device application	Sub billing Multi-tariff
Accuracy class	Class 1 active energy conforming to IEC 62053-21 Class B active energy conforming to EN 50470-1 Class B active energy conforming to EN 50470-3
Analogue input type	Direct input
Maximum current [I _{max}]	45 A
[I _b] basic current	5 A
Rated current	45 A
Rated voltage	230 V
Network frequency	50 Hz 60 Hz
Frequency measurement range	45...66 Hz
Technology type	Electronic
Display type	LCD display
Sampling rate	32 samples/cycle
Measurement current	0.25...45 A
Display digits	6
Maximum value measured	9999.99 kWh 99999.9 kWh
Information displayed	Tariff (2)

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Communication port protocol	Modbus RTU at 1200...9600 bit/s even/odd or none
Communication port support	Screw terminals: RS485
Local signalling	Red LED: metering and activity 10000, 2000, 1000, 100, 10, 1, 0.1 or 0.01 imp/kWh
Number of outputs	1 pulse energy monitoring:
Impulse duration	11.2...32 ms
[Us] rated supply voltage	195...253 V AC
Maximum power consumption in VA	10 VA at 240 V AC
Maximum power consumption in W	2 W per phase
[Uimp] rated impulse withstand voltage	6 kV 1.2/50 μ s
Mounting mode	Clip-on
Mounting support	DIN rail
Connections - terminals	Power circuit: tunnel type terminals (bottom) 8...10 mm ² cable(s) Power circuit: tunnel type terminals (top) 8...10 mm ² cable(s) Pulse output: screw clamp terminals (top) 2.5 mm ² cable(s) Communication: screw clamp terminals (bottom) 2.5 mm ² cable(s)
Tightening torque	Power circuit: 0.35 N.m flat screwdriver 2.2 mm Pulse output: 0.1 N.m flat screwdriver 1.3 mm Communication: 0.1 N.m flat screwdriver 1.3 mm
Wire stripping length	Power circuit: 7.5 mm Pulse output: 7 mm Communication: 7 mm
Standards	IEC 62053-21 IEC 62053-23 EN 50470-3
Product certifications	MID conforming to EN 50470-3 CE conforming to EN 50470-3 CE

Environment

IP degree of protection	IP51 front panel: conforming to IEC 60529 IP20 casing:
Ambient air temperature for operation	-40...70 °C
Ambient air temperature for storage	-40...80 °C
Operating altitude	< 2000 m
Relative humidity	0...75 % operation 0...95 % storage
Colour	White
9 mm pitches	2
Width	17.5 mm
Height	90 mm
Depth	63 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.600 cm
Package 1 Width	2.000 cm

Package 1 Length	10.000 cm
Package 1 Weight	88.900 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	7.800 cm
Package 2 Width	10.800 cm
Package 2 Length	22.000 cm
Package 2 Weight	951.000 g
Unit Type of Package 3	S03
Number of Units in Package 3	60
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	5.800 kg

Contractual warranty

Warranty (in months)	18
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint 28

Environmental Disclosure [Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic Yes

[EU RoHS Directive](#) Compliant

REACH Regulation [REACH Declaration](#)

Use Longer



Lifetime extension

Repair No

Use Again



Repack and remanufacture

End of life manual availability [End of Life Information](#)

Take-back No

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Technical Illustration

Assembly's dimensions

mm Without sealing cover/ Sans couvercle d'étanchéité/
 [in] Ohne Verschlussdeckel/ Senza coperchio di tenuta

