

Product datasheet

Specifications



APC Easy UPS On-Line, 1000VA/800W, Tower, 230V, 3x IEC C13 outlets, Intelligent Card Slot, LCD, Extended runtime

SRV1KIL

Price: 18,860.00 ZAR

Overview

Presentation	High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.
Lead time	Usually in Stock

Main

Main Input Voltage	230 V AC 1 phase
Input voltage	220 V 240 V
Input Connection Type	IEC 60320 C14
Input voltage limits	110...285 V half load 160...280 V full load
Network frequency	40...70 Hz auto sensing
Output voltage	230 V AC 1 phase
Output voltage	220 V 240 V
Rated power in W	800 W
rated power in VA	1000 VA
Output connection type	3 IEC 60320 C13
Bypass type	Internal bypass (automatic and manual)
Crest factor	3 : 1
Harmonic distortion	3 %
Maximum configurable power in VA	1000 VA
Maximum configurable power in W	800 W
UPS type	Double conversion online
Wave type	Sine wave
Efficiency	88 % (full load)
Output frequency	50/60 Hz +/- 3 Hz sync to mains

Complementary

Battery type	Lead-acid battery
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Battery voltage	36 V
Extended runtime	1

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	4.5 h
Battery life	3...5 year(s)
Battery charger power	175 W rated
Battery type	Lead-acid external included
Control panel	Multifunction LCD status and control console
Free slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
UPS connectivity	Serial port USB port Available expansion slot
Surge energy rate	600 J
Cable length	1.50 m
Number of cables	1
Colour	Black (RAL 7010)
Height	238 mm
Width	290 mm
Depth	400 mm
Net weight	24 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Not rack-mountable
USB compatible	No
Mounting position	Vertical
Mounting mode	Tower
Number of power module filled slots	0
Number of power module free slots	0
Redundant	No
Range of product	Easy UPS On-Line
Product or component type	Uninterruptible power supply (UPS)
Number of tare power	28 W
Curve equation	Efficiency
Curve fixed loss	0.0608
Curve load maximum	100 %
Curve load minimum	7 %
Curve proportional loss	0.0545
Curve square loss	0.0077
Curve test cond ID	Curve fit to measured efficiency data. All measurements taken in normal operating mode, at typical environmental conditions, with nominal electrical input and balanced resistive load (PF = 1.0) output.
Curve X-axis maximum	100 %

Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Show note OP temperature	No
Battery curve	D
Liquid value	0
Battery design life	2 year(s)
UPS design life	3 year(s)
Battery power in VAH	516 VAh runtime
Battery option	SRV36BP-9A 1 1032 VAh SRV36BP-9A 2 1548 VAh SRV36BP-9A 3 2064 VAh SRV36BP-9A 4 2580 VAh
UPS size	WS

Environment

Product certifications	CE UKCA EAC TISI
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-20...50 °C
Storage altitude	0...15000 m
IP degree of protection	IP20
Relative humidity	0...95 % non-condensing
Storage Relative Humidity	0...95 % non-condensing
Acoustic level	50 dBA
Heat dissipation	372 Btu/h
Operating altitude	0...3000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	2
Package 1 Height	35.5 cm
Package 1 Width	47 cm
Package 1 Length	52.5 cm
Package 1 Weight	26.7 kg

Contractual warranty

Warranty (in months)

24



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant

SCIP Number

B2b22a56-41f2-497e-9ea6-cf093b3b8bd3

REACH Regulation

[REACH Declaration](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

End of life manual availability

[End of Life Information](#)

Take-back

No

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative



