

Product datasheet

Specifications



energy sensor. PowerTag Monoconnect 630A 3P+N

LV434023

⚠ Discontinued on: 01 Dec 2024

⚠ To be discontinued

Price: 16,233.78 ZAR

Main

Range of product	PowerLogic
Product name	PowerTag M630
Product or component type	Energy sensor
Poles	3P + N
Maximum current [Imax]	630 A
[Ib] Basic current	100 A
Starting current	400 mA
Saturation current	1260 A
Product specific application	Energy management Overload alarm Power factor Load monitoring Circuit monitoring
Concentrator compatibility	EcoStruxure Panel Server Entry EcoStruxure Panel Server Universal EcoStruxure Panel Server Advanced Harmony Hub Acti9 Smartlink SI B Acti9 Smartlink SI D Acti9 PowerTag Link Acti9 PowerTag Link HD
Range compatibility	ComPacT ComPacT NSX NSX400 ComPacT ComPacT NSX NSX630 ComPacT ComPacT INS INS320 ComPacT Compact INV Interpact INV400 ComPacT Compact INV Interpact INV630 Compact NS Compact NS400 Compact NS Compact NS630 EasyPact EasyPact CVS400 EasyPact EasyPact CVS630 ComPacT ComPacT INS INS630
Type of measurement	Active and reactive energy Active and reactive power Apparent power Current Voltage Power factor
Accuracy class	Class 1 active energy conforming to IEC 61557-12 Class 2 reactive energy conforming to IEC 61557-12 Class 1 active power conforming to IEC 61557-12 Class 2 reactive power conforming to IEC 61557-12 Class 2 apparent power conforming to IEC 61557-12 Class 1 current conforming to IEC 61557-12 Class 0.5 voltage conforming to IEC 61557-12 Class 1 power factor conforming to IEC 61557-12

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Metering type	Power factor 0...1: class 1 at 25 °C conforming to IEC 61557-12 Active energy Ep IN/OUT/tot 0...281 x 10exp(9) kWh: class 1 at 25 °C conforming to IEC 61557-12 Reactive energy Ep IN/OUT/tot 0...281 x 10exp(9) kVARh: class 2 at 25 °C conforming to IEC 61557-12 Voltage U12, U23, U31 320...480 V: class 0.5 at 25 °C conforming to IEC 61557-12 Voltage V1N, V2N, V3N 184...276 V: class 0.5 at 25 °C conforming to IEC 61557-12 Current I1, I2, I3, Iavg 20...630 A: class 1 at 25 °C conforming to IEC 61557-12 Apparent power S, S1, S2, S3 221 VA...1048 kVA: class 2 at 25 °C conforming to IEC 61557-12 Active power P, P1, P2, P3 221 W...1048 kW: class 1 at 25 °C conforming to IEC 61557-12 Reactive power Q, Q1, Q2, Q3 221 VAR...1048 kVAR: class 2 at 25 °C conforming to IEC 61557-12 Frequency 45...65 Hz
Mounting location	Bottom
Mounting support	On circuit breaker
Connection pitch	45 mm
Product destination	Switchboard
Event management	Voltage loss with measured current at voltage loss
Transmission support medium	Radio frequency 2.4...2.4835 GHz conforming to IEEE 802.15.4 (11...26) transmission time < 5 ms
Emission power	10 mW

Complementary

[Imp] maximum permanent current	1.2 x In
Form factor	Monoconnect
Mounting mode	Bolt-on
Tightening torque	50 N.m
supply voltage	230 V AC, +/- 20 %, between phase and neutral 400 V AC, +/- 20 %, between phases
Network frequency	50 Hz 60 Hz
Maximum power consumption	3.7 VA
Standards	IEC 61557-12 IEC 61010-1 ETSI EN 301 489-1 IEC 61010-2-030 IEC 61326-1 ETSI EN 300 328
Product certifications	IEC DNV Marine
Height	91 mm
Width	185 mm
Depth	110 mm
Net weight	1000 g
Colour	Dark grey (RAL 7016)

Environment

Quality labels	CE
Directives	2014/53/EU - radio equipment directive
Operating altitude	0...2000 m

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C
Overvoltage category	IV conforming to IEC 61010-1
Measurement category	Category III conforming to IEC 61010-2-030
IP degree of protection	IP20
IK degree of protection	IK07 conforming to IEC 60068-2-75 test Ehb
Pollution degree	3
Relative humidity	0...95 % at 55 °C conforming to IEC 60721-3-3
Vibration resistance	3M4 conforming to IEC 60721-3-3
Electromagnetic compatibility	Industrial electromagnetic environment conforming to IEC 61326-1 Radiated EMC conforming to ETSI EN 301 489-17 Electromagnetic emission conforming to IEC 62311
environmental characteristics	Indoor use

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.000 cm
Package 1 Width	15.000 cm
Package 1 Length	21.000 cm
Package 1 Weight	1.312 kg
Unit Type of Package 2	S02
Number of Units in Package 2	2
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	3.034 kg
Unit Type of Package 3	P06
Number of Units in Package 3	32
Package 3 Height	73.000 cm
Package 3 Width	60.000 cm
Package 3 Length	80.000 cm
Package 3 Weight	60.544 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint 71

Environmental Disclosure [Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number B59c5c5a-aa9d-4410-93ab-f135cf374f64

REACH Regulation [REACH Declaration](#)

Use Longer



Lifetime extension

Repair No

Use Again



Repack and remanufacture

End of life manual availability [End of Life Information](#)

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Technical Illustration

Dimensions

