

# Product datasheet

Specifications



## Thermal overload relay, TeSys Deca, 95-120A, class 10A, for unbalanced loads

LR3D4367

### Main

Range	TeSys
Product name	TeSys LRD TeSys Deca
Product or component type	Non differential thermal overload relay
Device short name	LR3D
Relay application	Motor protection
Product compatibility	LC1D150 LC1D115
Network type	AC DC
Thermal overload class	Class 10A conforming to IEC 60947-4-1
Thermal protection adjustment range	95...120 A
[Ui] rated insulation voltage	Power circuit: 1000 V conforming to IEC 60947-4-1 Power circuit: 600 V conforming to CSA Power circuit: 600 V conforming to UL

### Complementary

Network frequency	0...400 Hz
Mounting support	Plate, with specific accessories Rail, with specific accessories Under contactor
Tripping threshold	1.14 +/- 0.06 I <sub>r</sub> conforming to IEC 60947-4-1
Auxiliary contact composition	1 NO + 1 NC
[I <sub>th</sub> ] conventional free air thermal current	5 A for signalling circuit
Permissible current	0.06 A at 440 V DC-13 for signalling circuit 0.12 A at 600 V AC-15 for signalling circuit
[U <sub>e</sub> ] rated operational voltage	1000 V AC 0...400 Hz for power circuit conforming to IEC 60947-4-1
Associated fuse rating	4 A gG for signalling circuit 4 A BS for signalling circuit
[U <sub>imp</sub> ] rated impulse withstand voltage	6 kV conforming to IEC 60947-1
Phase failure sensitivity	Tripping current 130 % of I <sub>r</sub> on two phase, the last one at 0
Control type	Red push-button: stop Blue push-button: reset
Temperature compensation	-20...60 °C

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

<b>Connections - terminals</b>	Power circuit: screw clamp terminals 1 cable(s) 4...35 mm <sup>2</sup> flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm <sup>2</sup> flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm <sup>2</sup> flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm <sup>2</sup> solid without cable end Power circuit: screw clamp terminals 1 cable(s) 4...50 mm <sup>2</sup> flexible without cable end Power circuit: screw clamp terminals 1 cable(s) 4...50 mm <sup>2</sup> solid without cable end
--------------------------------	---

<b>Tightening torque</b>	Control circuit: 1.7 N.m - on screw clamp terminals Power circuit: 9 N.m - on screw clamp terminals
--------------------------	--

<b>Net weight</b>	0.9 kg
-------------------	--------

## Environment

<b>Climatic withstand</b>	conforming to IACS E10
---------------------------	------------------------

<b>IP degree of protection</b>	IP20 conforming to IEC 60529
--------------------------------	------------------------------

<b>Ambient air temperature for operation</b>	-20...60 °C without derating conforming to IEC 60947-4-1
--	--

<b>Ambient air temperature for storage</b>	-60...70 °C
--	-------------

<b>Flame retardance</b>	V1 conforming to UL 94
-------------------------	------------------------

<b>Mechanical robustness</b>	Vibrations: 6 Gn conforming to IEC 60068-2-6 Shocks: 15 Gn for 11 ms conforming to IEC 60068-2-7
------------------------------	---

<b>Dielectric strength</b>	2.2 kV at 50 Hz conforming to IEC 60947-1
----------------------------	---

<b>Standards</b>	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 UL 60947-5-1 CSA C22.2 No 60947-4-1 CSA C22.2 No 60947-5-1 GB/T 14048.4 GB/T 14048.5 EN 50495
------------------	--

<b>Product certifications</b>	IEC UL CSA CCC EAC BV DNV-GL LROS (Lloyds register of shipping) ATEX INERIS
-------------------------------	---

## Packing Units

<b>Unit Type of Package 1</b>	PCE
-------------------------------	-----

<b>Number of Units in Package 1</b>	1
-------------------------------------	---

<b>Package 1 Height</b>	15.5 cm
-------------------------	---------

<b>Package 1 Width</b>	13.5 cm
------------------------	---------

<b>Package 1 Length</b>	11.0 cm
-------------------------	---------

<b>Package 1 Weight</b>	880.0 g
-------------------------	---------

## Contractual warranty

<b>Warranty (in months)</b>	18
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint 14 kg CO2 eq.

Environmental Disclosure [Product Environmental Profile](#)

## Use Better



### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic Yes

[EU RoHS Directive](#) Compliant

REACH Regulation [REACH Declaration](#)

## Use Longer



### Lifetime extension

Repair No


## Use Again



### Repack and remanufacture

End of life manual availability [End of Life Information](#)

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins