

# Product datasheet

Specifications



APC Smart-UPS On-Line,  
1000VA, Lithium-ion, Rackmount  
4U, 230V, 8x C13 IEC outlets,  
Network Card, Extended long  
runtime, Rail kit included

SRTL1000RM4UXLI-NC

**Price: 92,000.00 ZAR**

## Overview

Presentation	High density, double-conversion on-line power protection with long runtime with NMC
Lead time	Usually in Stock

## Main

Main Input Voltage	230 V AC 1 phase
Input voltage	220 V
Input Connection Type	IEC 60320 C14
Input voltage limits	160...275 V
Network frequency	40...70 Hz auto-sensing
Output voltage	230 V AC 1 phase
Output voltage	220 V
Rated power in W	900 W
rated power in VA	1000 VA
Output connection type	8 IEC 60320 C13
Bypass type	Built-in bypass
Crest factor	3 : 1
Harmonic distortion	Less than 2 %
Maximum configurable power in VA	1000 VA
Maximum configurable power in W	900 W
UPS type	Double conversion online
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

## Complementary

Battery type	Li-Ion (Lithium-Ion)
Battery voltage	48 V
Extended runtime	1
Number of battery filled slots	0
Number of battery free slots	0
Battery life	5...10 year(s)

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

<b>Battery charger power</b>	103 W rated
<b>Battery type</b>	Li-Ion (Lithium-Ion) internal included
<b>Emergency power off</b>	Yes
<b>Free slots</b>	0
<b>Preinstalled device</b>	Network management card 3 with environmental monitoring
<b>Alarm</b>	Audible and visible alarms : prioritized by severity
<b>UPS connectivity</b>	Serial port USB port Pre-installed network management card 3
<b>Surge energy rate</b>	340 J
<b>Number of rack unit</b>	4U
<b>Cable length</b>	1.8 m
<b>Number of cables</b>	1
<b>Colour</b>	Black with silver front bezel
<b>Height</b>	85 mm
<b>Width</b>	432 mm
<b>Depth</b>	560 mm
<b>Net weight</b>	13.7 kg
<b>Mounting preference</b>	No preference
<b>Mounting mode</b>	Rack-mounted with kit
<b>Two post mountable</b>	0
<b>USB compatible</b>	Yes
<b>Mounting position</b>	Horizontal Vertical
<b>Mounting mode</b>	Rack-mounted with included kit
<b>Number of power module filled slots</b>	0
<b>Number of power module free slots</b>	0
<b>Additional specification</b>	Lithium-Ion
<b>Redundant</b>	No
<b>Range of product</b>	Smart-UPS On-Line
<b>Product or component type</b>	Uninterruptible power supply (UPS)

## Environment

<b>Product certifications</b>	CE UK PSTI
<b>Marking</b>	CE Mark
<b>Ambient air temperature for operation</b>	0...40 °C
<b>Ambient air temperature for storage</b>	-15...45 °C
<b>Storage altitude</b>	0...15240 m
<b>IP degree of protection</b>	IP20
<b>Relative humidity</b>	0...95 % non-condensing
<b>Storage Relative Humidity</b>	0...95 % non-condensing

---

Acoustic level	50 dBA
Heat dissipation	400 Btu/h
Operating altitude	0...10000 ft

---

## Packing Units

---

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.5 cm
Package 1 Width	60 cm
Package 1 Length	81 cm
Package 1 Weight	21 kg

---

## Contractual warranty

---

Warranty (in months)	60
----------------------	----

---



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better



### Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant with Exemptions

SCIP Number

8519b6fb-f7a9-44f8-be44-5dee68362126

REACH Regulation

[REACH Declaration](#)



### Energy efficiency

Product contributes to saved and avoided emissions

Yes

## Use Longer



### Lifetime extension

Repair

No

## Use Again



### Repack and remanufacture

End of life manual availability

[End of Life Information](#)

Removable battery

User replaceable

Take-back

No

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

---







