

Product datasheet

Specifications



APC DIN Rail - Panel Mount UPS- without Battery-500VA 230V

SUA500PDR1

Price: 11,757.60 ZAR

Overview

Presentation	Proven Industrial UPS power protection for control applications and harsh environments.
Lead time	Usually in Stock

Main

Main Input Voltage	230 V
Input voltage	220 V 240 V
Input voltage limits	151...302 V adjustable 160...285 V
Number of input connectors	1 hard wire 3-wire (1P + N + E)
Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Output voltage	230 V
Output voltage	220 V 240 V
Rated power in W	325 W
rated power in VA	500 VA
Output connector type	Hard wire 3-wire (H N + E) for 1 zone(s)
Harmonic distortion	Less than 5 %
Maximum configurable power in VA	500 VA
Maximum configurable power in W	325 W
UPS type	Line interactive
Efficiency	94 % (full load)
Output frequency	47...53 Hz for 50 Hz nominal sync to mains 57...63 Hz for 60 Hz nominal sync to mains

Complementary

Battery voltage	24 V
Extended runtime	0
Battery capacity	5.0 Ah
Number of battery filled slots	0
Number of battery free slots	0
Control panel	LED status display with load and battery bar-graphs and on line : on battery : replace battery : and overload indicators
Emergency power off	Yes

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Free slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Surge energy rate	540 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449
Height	148 mm
Width	362 mm
Depth	171 mm
Net weight	8.18 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No
Provided equipment	CD with software Documentation CD Installation guide Smart UPS signalling RS-232 cable
Number of power module filled slots	0
Number of power module free slots	0
Redundant	No
Product or component type	Uninterruptible power supply (UPS)
Performance multiplier	1
Value multiplier	1
Curve equation	Efficiency
Curve load maximum	100 %
Curve X-axis maximum	100 %
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Show note OP temperature	No
Battery curve	B
Liquid value	0
Battery power in VAH	0 VAh runtime
UPS size	WS

Environment

Product certifications	CE VDE
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0...15240 m
IP degree of protection	IP20
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %
Acoustic level	55 dBA
Heat dissipation	90 Btu/h
Operating altitude	0...10000 ft

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	29.7 cm
Package 1 Width	48.1 cm
Package 1 Length	29.7 cm
Package 1 Weight	9.55 kg

Contractual warranty

Warranty (in months)	24
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint 442

Environmental Disclosure [Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

REACH Regulation [REACH Declaration](#)

Use Longer



Lifetime extension

Repair No

Use Again



Repack and remanufacture

End of life manual availability [End of Life Information](#)

Removable battery User replaceable

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins