

Product datasheet

Specifications



A9MEM3155. iEM3155 energy meter. 63 A. Modbus. 1 digital I. 1 digital O. multi-tariff. MID

A9MEM3155

Price: 6,597.35 ZAR

Main

| | |
|---------------------------|---------------|
| Range | Acti9 |
| range of product | Acti9 iEM3000 |
| Product or component type | Energy meter |
| Device short name | iEM3155 |

| | |
|----------------|--|
| Market segment | Buildings small building cost management: billing: main incomer Buildings small building cost management: billing: sub feeder Buildings small building cost management: billing: panelboard Buildings medium building cost management: billing: main incomer Buildings medium building cost management: billing: sub feeder Buildings medium building cost management: billing: panelboard Buildings large building cost management: billing: main incomer Buildings large building cost management: billing: sub feeder Buildings large building cost management: billing: panelboard Buildings multi-site cost management: billing: main incomer Buildings multi-site cost management: billing: sub feeder Buildings multi-site cost management: billing: panelboard Data center cost management: billing Healthcare cost management: billing Industry cost management: billing Buildings small building cost management: cost allocation: main incomer Buildings small building cost management: cost allocation: sub feeder Buildings small building cost management: cost allocation: panelboard Buildings medium building cost management: cost allocation: main incomer Buildings medium building cost management: cost allocation: sub feeder Buildings medium building cost management: cost allocation: panelboard Buildings large building cost management: cost allocation: main incomer Buildings large building cost management: cost allocation: sub feeder Buildings large building cost management: cost allocation: panelboard Buildings multi-site cost management: cost allocation: main incomer Buildings multi-site cost management: cost allocation: sub feeder Buildings multi-site cost management: cost allocation: panelboard Data center cost management: cost allocation Healthcare cost management: cost allocation Industry cost management: cost allocation |
|----------------|--|

Complementary

| | |
|---------------------|--|
| Poles description | 3P + N 1P + N 3P |
| Type of measurement | Active and reactive energy Active and reactive power Current Voltage |
| Metering type | Active, reactive, apparent energy (signed, four quadrant) |
| Device application | Multi-tariff Sub billing Partial meter |
| Accuracy class | Class 1 active energy conforming to IEC 62053-21 Class 1 active energy conforming to IEC 61557-12 Class B active energy conforming to EN 50470-3 |

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

| | |
|------------------------------------|--|
| input type | Direct connection |
| [In] rated current | 63 A |
| Rated voltage | 100...277 V 173...480 V |
| Network frequency | 60 Hz 50 Hz |
| Technology type | Electronic |
| Display type | LCD display |
| Sampling rate | 32 samples/cycle |
| Measurement current | 0...63 A |
| Maximum value measured | 99999999.9 kWh |
| tariff input | Tariff (4) |
| Communication port protocol | Modbus RTU at 9.6, 19.2 and 38.4 kbauds even/odd or none, insulation 4000 V |
| Communication port support | Screw terminal block: RS485 |
| Local signalling | Green indicator light: power ON Yellow flashing LED: accuracy checking alarm: overload Yellow indicator light: communications are active on the Modbus port (Modbus) |
| Number of inputs | 1 digital 0...5 V/11...40 V 24 V DC |
| Number of outputs | 1 digital (static) |
| Output voltage | 5...40 V DC@50 mA |
| Mounting mode | Clip-on |
| Mounting support | DIN rail |
| Connections - terminals | Screw terminals 16 mm ² cable(s) |
| Overvoltage category | III |
| Standards | BS EN 61557-12:2021 IEC 61557-12:2021 EN 61557-12:2021 BS EN 61326-1 IEC 61326-1 EN 61326-1 BS EN 62052-11:2020 IEC 62052-11:2020 EN 62052-11:2020 BS EN 62053-21 IEC 62053-21 EN 62053-21 BS EN 62052-23 IEC 62053-23:2020 EN 62052-23 BS EN 62052-31:2015 IEC 62052-31:2015 EN 62052-31:2015 BS EN 61010-1:2010 EN 61010-1:2010 IEC 61010-1:2010 UL 61010-1:2010 BS EN 61010-2-30 IEC 61010-2-30 EN 61010-2-30 UL 61010-2-30 BS EN 50470-3 EN 50470-3 BS EN 50470-1 EN 50470-1 ANSI C12.16 |

| | |
|-------------------------------|--|
| Product certifications | CE conforming to IEC 61010-1 (safety) CE conforming to EN 61557-12 (power monitor) CE conforming to EN/IEC 61326-1 (EMC) UKCA conforming to BS EN 61010-1 (safety) UKCA conforming to BS EN 61557-12 (power monitor) UKCA conforming to BS EN 61326-1 (EMC) CULus conforming to UL 61010-1 (safety) CULus conforming to EN 61010-1 (safety) EAC conforming to EN 50470-3 (sub-meter) RCM conforming to EN 62052 (sub-meter) KZ conforming to EN 50470-3 (sub-meter) METAS conforming to EN 50470-1 (sub-meter) MID conforming to EN 50470-3 (sub-meter) MID conforming to EN 50470-1 (sub-meter) NMI conforming to NMI M 6-1 |
| Market segment | Small commercial Residential |
| Compatibility code | IEM3155 |

Environment

| | |
|--|---|
| IP degree of protection | IP40 front panel: conforming to IEC 60529 IP20 body: conforming to IEC 60529 |
| Pollution degree | 2 |
| Relative humidity | 5...95 % at 50 °C |
| Ambient air temperature for operation | -25...55 °C - MID -25...70 °C - IEC -25...60 °C - IEC |
| Ambient air temperature for storage | -40...85 °C |
| Operating altitude | < 3000 m |
| Colour | White |
| 9 mm pitches | 10 |
| Width | 90 mm |
| Height | 95 mm |
| Depth | 69 mm |

Packing Units

| | |
|-------------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 8.500 cm |
| Package 1 Width | 9.500 cm |
| Package 1 Length | 10.500 cm |
| Package 1 Weight | 460.400 g |
| Unit Type of Package 2 | S03 |
| Number of Units in Package 2 | 30 |
| Package 2 Height | 30.000 cm |
| Package 2 Width | 30.000 cm |
| Package 2 Length | 40.000 cm |
| Package 2 Weight | 14.212 kg |

Contractual warranty



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint 63

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number Ac5c87cb-7cc2-4c71-90bc-47e5bdbaf2db

REACH Regulation [REACH Declaration](#)

Halogen-free status Halogen free plastic parts product

Use Longer

Lifetime extension

Repair No

Use Again

Repack and remanufacture

End of life manual availability [End of Life Information](#)

Take-back No

WEEE Label The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Technical Illustration

User interface / product ON

