

# Product datasheet

Specifications



APC Easy UPS On-Line, 2000VA/1600W, Rackmount 4U, 230V, 4x IEC C13 outlets, Intelligent Card Slot, LCD, Extended runtime, W/ rail kit

SRV2KRILRK

**Price: 35,880.00 ZAR**

## Overview

<b>Presentation</b>	High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.
<b>Lead time</b>	Usually in Stock

## Main

<b>Main Input Voltage</b>	230 V AC 1 phase
<b>Input voltage</b>	220 V 240 V
<b>Input Connection Type</b>	IEC 60320 C14
<b>Input voltage limits</b>	110...285 V half load 160...280 V full load
<b>Network frequency</b>	40...70 Hz auto sensing
<b>Output voltage</b>	230 V AC 1 phase
<b>Output voltage</b>	220 V 240 V
<b>Rated power in W</b>	1600 W
<b>rated power in VA</b>	2000 VA
<b>Output connection type</b>	4 IEC 60320 C13
<b>Bypass type</b>	Internal bypass (automatic and manual)
<b>Crest factor</b>	3 : 1
<b>Harmonic distortion</b>	3 %
<b>Maximum configurable power in VA</b>	2000 VA
<b>Maximum configurable power in W</b>	1600 W
<b>UPS type</b>	Double conversion online
<b>Wave type</b>	Sine wave
<b>Half load runtime</b>	00:12:00 800 W
<b>Efficiency</b>	88 % (full load)
<b>Output frequency</b>	50/60 Hz +/- 3 Hz sync to mains

## Complementary

<b>Battery type</b>	Lead-acid battery
<b>Additional information</b>	Configurable for 220 : 230 or 240 nominal output voltage

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

<b>Battery voltage</b>	72 V
<b>Extended runtime</b>	1
<b>Number of battery filled slots</b>	1
<b>Number of battery free slots</b>	0
<b>Battery recharge time</b>	5.5 h
<b>Battery life</b>	3...5 year(s)
<b>Battery charger power</b>	350 W rated
<b>Battery type</b>	Lead-acid external included
<b>Control panel</b>	Multifunction LCD status and control console
<b>Alarm</b>	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
<b>UPS connectivity</b>	Serial port USB port Available expansion slot
<b>Surge energy rate</b>	600 J
<b>Number of rack unit</b>	4U
<b>Number of cables</b>	1
<b>Colour</b>	Black (RAL 7010)
<b>Height</b>	172 mm
<b>Width</b>	437 mm
<b>Depth</b>	632 mm
<b>Net weight</b>	51.7 kg
<b>Mounting location</b>	Front
<b>Mounting preference</b>	Lower
<b>Mounting mode</b>	Rack-mounted
<b>USB compatible</b>	No
<b>Mounting position</b>	Horizontal
<b>Mounting mode</b>	Rack-mounted with included kit
<b>Number of power module filled slots</b>	0
<b>Number of power module free slots</b>	0
<b>Redundant</b>	No
<b>Range of product</b>	Easy UPS On-Line
<b>Product or component type</b>	Uninterruptible power supply (UPS)
<b>Number of tare power</b>	40 W
<b>Curve equation</b>	Efficiency
<b>Curve fixed loss</b>	0.0303
<b>Curve load maximum</b>	100 %
<b>Curve load minimum</b>	4 %
<b>Curve proportional loss</b>	0.0482
<b>Curve square loss</b>	0.0248
<b>Curve test cond ID</b>	Curve fit to measured efficiency data. All measurements taken in normal operating mode, at typical environmental conditions, with nominal electrical input and balanced resistive load (PF = 1.0) output.

Curve X-axis maximum	100 %
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Show note OP temperature	No
Battery curve	D
Liquid value	0
Battery design life	2 year(s)
UPS design life	3 year(s)
Battery power in VAH	972 VAh runtime
Battery option	SRV72RLBP-9A 1 1944 VAh SRV72RLBP-9A 2 2916 VAh SRV72RLBP-9A 3 3888 VAh SRV72RLBP-9A 4 4860 VAh
UPS size	WS

## Environment

Product certifications	CE UKCA EAC TISI
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-20...50 °C
Storage altitude	0...15000 m
IP degree of protection	IP20
Relative humidity	0...95 % non-condensing
Storage Relative Humidity	0...95 % non-condensing
Acoustic level	50 dBA
Heat dissipation	745 Btu/h
Operating altitude	0...3000 m

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	3
Package 1 Height	48 cm
Package 1 Width	60 cm
Package 1 Length	70 cm

---

Package 1 Weight	66.5 kg
------------------	---------

## Contractual warranty

---

Warranty (in months)	24
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

<b>Materials and Substances</b>	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
<a href="#">EU RoHS Directive</a>	Compliant with Exemptions
REACH Regulation	<a href="#">REACH Declaration</a>

### Use Longer

<b>Lifetime extension</b>	
Repair	No

### Use Again

<b>Repack and remanufacture</b>	
End of life manual availability	<a href="#">End of Life Information</a>
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

---



