

Product datasheet

Specifications



APC Smart-UPS, Line Interactive, 1500VA, Tower, 230V, 8x IEC C13 outlets, SmartSlot, AVR, LCD

SMT1500I

Price: 15,437.60 ZAR

Overview

Presentation Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.

Lead time Usually Ships within 2 Weeks

Main

Main Input Voltage 230 V AC 1 phase

Input voltage 220 V
240 V

Input Connection Type IEC 320 C14

Input voltage limits 151...302 V adjustable
160...286 V

Network frequency 50/60 Hz +/- 3 Hz auto-sensing

Output voltage 230 V AC 1 phase

Output voltage 220 V
240 V

Rated power in W 1000 W

rated power in VA 1500 VA

Output connection type 8 IEC 320 C13
2 IEC Jumpers

Harmonic distortion Less than 5 % at full load

Maximum configurable power in VA 1500 VA

Maximum configurable power in W 1000 W

UPS type Line interactive

Wave type Sine wave

Output frequency 47...53 Hz for 50 Hz nominal sync to mains
57...63 Hz for 60 Hz nominal sync to mains

Complementary

Battery type Lead-acid battery

Additional information Configurable for 220 : 230 or 240 nominal output voltage

Extended runtime 0

Number of battery filled slots 0

Number of battery free slots 0

Battery recharge time 3 h

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Number of battery replacement quantity	1
Battery life	3...5 year(s)
Battery charger power	136 W rated
Battery type	Lead-acid internal included
Control panel	Multifunction LCD status and control console
Free slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
UPS connectivity	Serial port USB port Available expansion slot
Surge energy rate	459 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449
Cable length	1.8 m
Number of cables	1
Colour	Black
Height	219 mm
Width	171 mm
Depth	439 mm
Net weight	24.09 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No
Mounting mode	Tower
Provided equipment	USB cable Documentation CD Installation guide Smart UPS signalling RS-232 cable
Number of power module	0
Number of power module filled slots	0
Number of power module free slots	0
Redundant	No
Range of product	Smart-UPS
Product or component type	Uninterruptible power supply (UPS)
Performance multiplier	1
Number of tare power	30 W
Value multiplier	1
Size UPS version	Internetworking Server Telecom
Curve equation	Efficiency

Curve fixed loss	0.0101
Curve load maximum	100 %
Curve load minimum	2 %
Curve proportional loss	0
Curve square loss	0.0034
Curve test cond ID	Curve fit of data measured in accordance with the ENERGY STAR Test Method for Uninterruptible Power Supplies. All measurements taken in normal mode(s), at typical environmental conditions, with 230V/50Hz electrical input and balanced resistive load (PF = 1.0) output.
Curve X-axis maximum	100 %
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Show note OP temperature	No
Battery curve	Z
Liquid value	0
Battery power in VAH	408 VAh runtime
UPS size	S

Environment

Product certifications	CE EAC RCM VDE
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0...15240 m
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %
Acoustic level	45 dBA
Heat dissipation	135 Btu/h
Operating altitude	0...10000 ft

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	32.800 cm

Package 1 Width	37.600 cm
Package 1 Length	59.500 cm
Package 1 Weight	27.230 kg
Unit Type of Package 2	P12
Number of Units in Package 2	9
Package 2 Height	117.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	252.000 kg
SCC14	731304268680

Contractual warranty

Warranty (in months)	24 Battery 36 UPS
----------------------	-------------------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint 1111

Use Better



Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number B2b22a56-41f2-497e-9ea6-cf093b3b8bd3

REACH Regulation [REACH Declaration](#)



Energy efficiency

Energy Efficiency Optimized Energy efficient product

Use Longer



Lifetime extension

Repair No

Use Again



Repack and remanufacture

End of life manual availability [End of Life Information](#)

Removable battery User replaceable

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

