

# Product datasheet

Specifications



## APC Easy UPS, 2200VA, Tower, 230V, 4x CEE 7/3 Schuko outlets, AVR

BVX2200LI-GR

⚠ Discontinued on: 01 Dec 2024

⚠ To be discontinued

**Price: 5,519.82 ZAR**

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage	230 V AC 1 phase
Input Connection Type	Schuko
Cos phi	0.54
Input voltage limits	140...300 V 230 V AC
Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Output voltage	230 V AC 1 phase
Rated power in W	1200 W
rated power in VA	2200 VA
Output connection type	4 Schuko
Maximum configurable power in VA	2200 VA
Maximum configurable power in W	1200 W
Transfer time	6 ms typical : 10 ms maximum
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Full load runtime	00:01:00 1200 W
Half load runtime	00:08:30 600 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains

### Complementary

Battery capacity	9.0 Ah
Battery type	Lead-acid internal included
Control panel	LED Status display with on line : on battery
Surge energy rate	273 J
Cable length	1.2 m
Number of cables	1
Colour	Black
Height	190 mm



Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"


<b>Width</b>	140 mm
<b>Depth</b>	390 mm
<b>Net weight</b>	12.2 kg
<b>Mounting support</b>	Floor
<b>Mounting preference</b>	No preference
<b>Mounting mode</b>	Not rack-mountable
<b>Two post mountable</b>	0
<b>USB compatible</b>	No
<b>Mounting mode</b>	Desktop installation compact
<b>Provided equipment</b>	User manual
<b>Max runtime</b>	240 min
<b>Number of power module filled slots</b>	0
<b>Number of power module free slots</b>	0
<b>Redundant</b>	No
<b>Range of product</b>	Easy UPS
<b>Product or component type</b>	Uninterruptible power supply (UPS)

## Environment

<b>Product certifications</b>	CE CB
<b>Standards</b>	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
<b>Ambient air temperature for operation</b>	0...40 °C
<b>Ambient air temperature for storage</b>	-15...40 °C
<b>Storage altitude</b>	0...3000 m
<b>IP degree of protection</b>	IP20
<b>Relative humidity</b>	0...95 % non-condensing
<b>Storage Relative Humidity</b>	0...95 % non-condensing
<b>Acoustic level</b>	40 dBA
<b>Operating altitude</b>	0...3000 m

## Batteries & Runtime

<b>Run Time</b>	<a href="#">View Runtime Graph</a> 
<b>Efficiency</b>	<a href="#">View Efficiency Graph</a> 
<b>Battery type</b>	Lead-acid battery
<b>Battery voltage</b>	24 V
<b>Battery graph comments</b>	Curve fit to measured runtime data. All measurements taken with new, fully charged batteries, at typical environmental conditions, with no electrical input and balanced resistive load (PF = 1.0) output.
<b>Extended runtime</b>	0
<b>Number of battery filled slots</b>	0
<b>Number of battery free slots</b>	0

Battery recharge time	8 h
Battery life	2...3 year(s)
Replacement battery	<a href="#">APCRBC177</a> 

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	29.7 cm
Package 1 Width	49.5 cm
Package 1 Length	23.5 cm
Package 1 Weight	13.2 kg
SCC14	10731304404627

## Contractual warranty

Warranty (in months)	24
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better



### Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant

SCIP Number

Ef3b165e-8e1d-4ef1-89c3-03b78b282225

REACH Regulation

[REACH Declaration](#)

## Use Longer



### Lifetime extension

Repair

No

## Use Again



### Repack and remanufacture

End of life manual availability

[End of Life Information](#)

Removable battery

User replaceable

Take-back

No

Image of product / Alternate images

Alternative

---

