

# Product datasheet

Specifications



## LUB12 - Power base. TeSys U. 3P. 12A/690V

LUB12

**Price: 1,844.99 ZAR**

### Main

Range	TeSys
Product name	TeSys Ultra
Device short name	LUB
Product or component type	Non reversing power base
Device application	Motor control Motor protection
Poles description	3P
Suitability for isolation	Yes
[Ue] rated operational voltage	690 V AC for power circuit
Network frequency	40...60 Hz
[Ith] conventional free air thermal current	12 A
[Ie] rated operational current	12 A at <= 440 V 12 A at 500 V 9 A at 690 V
Utilisation category	AC-43 AC-44 AC-41
[Ics] rated service breaking capacity	50 kA at 230 V 50 kA at 440 V 10 kA at 500 V 4 kA at 690 V
Auxiliary contact composition	1 NO + 1 NC
Auxiliary contacts type	type linked contacts (1 NO + 1 NC) conforming to IEC 60947-4-1 type mirror contact (1 NC) conforming to IEC 60947-1
[Uc] control circuit voltage	24 V AC 50/60 Hz 24 V DC 48...72 V AC 50/60 Hz 48...72 V DC 110...240 V AC 50/60 Hz 110...220 V DC

### Complementary

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

<b>Typical current consumption</b>	<p>130 mA at 24 V DC I maximum while closing with LUCA, LUCB, LUCC, LUCD</p> <p>140 mA at 24 V AC I maximum while closing with LUCA, LUCB, LUCC, LUCD</p> <p>150 mA at 24 V DC I maximum while closing with LUCM</p> <p>280 mA at 110...220 V DC I maximum while closing with LUCA, LUCB, LUCC, LUCD</p> <p>280 mA at 110...240 V AC I maximum while closing with LUCA, LUCB, LUCC, LUCD</p> <p>280 mA at 48...72 V AC I maximum while closing with LUCA, LUCB, LUCC, LUCD</p> <p>280 mA at 48...72 V DC I maximum while closing with LUCA, LUCB, LUCC, LUCD</p> <p>35 mA at 110...220 V DC I rms sealed with LUCA, LUCB, LUCC, LUCD</p> <p>35 mA at 110...240 V AC I rms sealed with LUCA, LUCB, LUCC, LUCD</p> <p>35 mA at 48...72 V AC I rms sealed with LUCA, LUCB, LUCC, LUCD</p> <p>35 mA at 48...72 V DC I rms sealed with LUCA, LUCB, LUCC, LUCD</p> <p>60 mA at 24 V DC I rms sealed with LUCA, LUCB, LUCC, LUCD</p> <p>70 mA at 24 V AC I rms sealed with LUCA, LUCB, LUCC, LUCD</p> <p>70 mA at 24 V DC I rms sealed with LUCM</p>
<b>Heat dissipation</b>	<p>2 W for control circuit with LUCA, LUCB, LUCC, LUCD</p> <p>1.7 W for control circuit with LUCM</p>
<b>Safety reliability level</b>	<p>B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1</p> <p>B10d = 2000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1</p>
<b>Operating time</b>	<p>35 ms opening with LUCA, LUCB, LUCC, LUCD, LUCM for control circuit</p> <p>50 ms at &gt;= 72 V closing with LUCA, LUCB, LUCC, LUCD for control circuit</p> <p>60 ms at 48 V closing with LUCA, LUCB, LUCC, LUCD for control circuit</p> <p>70 ms at 24 V closing with LUCA, LUCB, LUCC, LUCD for control circuit</p> <p>75 ms closing with LUCM for control circuit</p>
<b>Mechanical durability</b>	15 Mcycles
<b>maximum operating rate</b>	3600 cyc/h
<b>Product certifications</b>	<p>CE</p> <p>UL</p> <p>CSA</p> <p>CCC</p> <p>EAC</p> <p>ASEFA</p> <p>ATEX</p> <p>Marine</p>
<b>Standards</b>	<p>EN 60947-6-2</p> <p>IEC 60947-6-2</p> <p>UL 60947-4-1, with phase barrier</p> <p>CSA C22.2 No 60947-4-1, with phase barrier</p>
<b>[Ui] rated insulation voltage</b>	<p>690 V conforming to IEC 60947-6-2 (pollution degree 3)</p> <p>600 V conforming to UL 60947-4-1</p> <p>600 V conforming to CSA C22.2 No 60947-4-1</p>
<b>[Uimp] rated impulse withstand voltage</b>	6 kV conforming to IEC 60947-6-2
<b>Safe separation of circuit</b>	<p>400 V SELV between the control and auxiliary circuits conforming to IEC 60947-1 appendix N</p> <p>400 V SELV between the control or auxiliary circuit and the main circuit conforming to IEC 60947-1 appendix N</p>
<b>Fixing mode</b>	<p>Clipped (DIN rail)</p> <p>Screw-fixed (plate)</p>
<b>Connections - terminals</b>	<p>Control circuit: screw clamp terminals 1 cable(s) 0.34...1.5 mm<sup>2</sup> flexible with cable end</p> <p>Control circuit: screw clamp terminals 1 cable(s) 0.75...1.5 mm<sup>2</sup> flexible without cable end</p> <p>Control circuit: screw clamp terminals 1 cable(s) 0.75...1.5 mm<sup>2</sup> rigid</p> <p>Control circuit: screw clamp terminals 2 cable(s) 0.34...1.5 mm<sup>2</sup> flexible with cable end</p> <p>Control circuit: screw clamp terminals 2 cable(s) 0.75...1.5 mm<sup>2</sup> flexible without cable end</p> <p>Control circuit: screw clamp terminals 2 cable(s) 0.75...1.5 mm<sup>2</sup> rigid</p> <p>Power circuit: screw clamp terminals 1 cable(s) 1...10 mm<sup>2</sup> rigid</p> <p>Power circuit: screw clamp terminals 1 cable(s) 1...6 mm<sup>2</sup> flexible with cable end</p> <p>Power circuit: screw clamp terminals 1 cable(s) 2.5...10 mm<sup>2</sup> flexible without cable end</p> <p>Power circuit: screw clamp terminals 2 cable(s) 1...6 mm<sup>2</sup> flexible with cable end</p> <p>Power circuit: screw clamp terminals 2 cable(s) 1...6 mm<sup>2</sup> rigid</p> <p>Power circuit: screw clamp terminals 2 cable(s) 1.5...6 mm<sup>2</sup> flexible without cable end</p>

<b>Tightening torque</b>	Control circuit: 0.8...1.2 N.m flat screwdriver 5 mm Control circuit: 0.8...1.2 N.m Philips no 1 screwdriver 5 mm Power circuit: 1.9...2.5 N.m flat screwdriver 6 mm Power circuit: 1.9...2.5 N.m Philips No 2 screwdriver 6 mm Power circuit: 1.9...2.5 N.m pozidriv No 2 screwdriver 6 mm
<b>Width</b>	45 mm
<b>Height</b>	154 mm
<b>Depth</b>	126 mm
<b>Net weight</b>	0.9 kg
<b>Compatibility code</b>	LUB

## Environment

<b>IP degree of protection</b>	IP20 conforming to IEC 60947-1 (front panel and wired terminals) IP20 conforming to IEC 60947-1 (other faces) IP40 conforming to IEC 60947-1 (front panel outside connection zone)
<b>Protective treatment</b>	TH conforming to IEC 60068
<b>Ambient air temperature for operation</b>	-25...60 °C with LUCM -25...70 °C with LUCA, LUCB, LUCC, LUCD
<b>Ambient air temperature for storage</b>	-40...85 °C
<b>Fire resistance</b>	960 °C parts supporting live components conforming to IEC 60695-2-12 650 °C conforming to IEC 60695-2-12
<b>Operating altitude</b>	2000 m
<b>Shock resistance</b>	10 gn power poles open conforming to IEC 60068-2-27 15 gn power poles closed conforming to IEC 60068-2-27
<b>Vibration resistance</b>	2 gn (f= 5...300 Hz) power poles open conforming to IEC 60068-2-27 4 gn (f= 5...300 Hz) power poles closed conforming to IEC 60068-2-27
<b>Resistance to electrostatic discharge</b>	8 kV level 3 in open air conforming to IEC 61000-4-2 8 kV level 4 on contact conforming to IEC 61000-4-2
<b>Non-dissipating shock wave</b>	1 kV serial mode 24...240 V AC conforming to IEC 60947-6-2 1 kV serial mode 48...220 V DC conforming to IEC 60947-6-2 2 kV common mode 24...240 V AC conforming to IEC 60947-6-2 2 kV common mode 48...220 V DC conforming to IEC 60947-6-2
<b>Resistance to fast transients</b>	2 kV class 3 serial link conforming to IEC 61000-4-4 4 kV class 4 all circuits except for serial link conforming to IEC 61000-4-4
<b>Resistance to radiated fields</b>	10 V/m 3 conforming to IEC 61000-4-3
<b>Immunity to radioelectric fields</b>	10 V conforming to IEC 61000-4-6
<b>Immunity to microbreaks</b>	3 ms for control circuit
<b>Immunity to voltage dips</b>	70 % / 500 ms conforming to IEC 61000-4-11

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	5.200 cm
<b>Package 1 Width</b>	13.500 cm
<b>Package 1 Length</b>	17.000 cm
<b>Package 1 Weight</b>	844.000 g
<b>Unit Type of Package 2</b>	S02
<b>Number of Units in Package 2</b>	10

<b>Package 2 Height</b>	15.000 cm
<b>Package 2 Width</b>	30.000 cm
<b>Package 2 Length</b>	40.000 cm
<b>Package 2 Weight</b>	8.698 kg
<b>Unit Type of Package 3</b>	P06
<b>Number of Units in Package 3</b>	160
<b>Package 3 Height</b>	75.000 cm
<b>Package 3 Width</b>	60.000 cm
<b>Package 3 Length</b>	80.000 cm
<b>Package 3 Weight</b>	147.668 kg

## **Contractual warranty**

<b>Warranty (in months)</b>	18
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Total lifecycle Carbon footprint 25

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic Yes

[EU RoHS Directive](#) Compliant

SCIP Number 61f5a085-dfde-4214-b2cf-ba3cfe0c33b4

REACH Regulation [REACH Declaration](#)

Halogen-free status Product contains halogen above thresholds

PVC free Yes

## Use Longer

### Lifetime extension

Repair No

## Use Again

### Repack and remanufacture

End of life manual availability [End of Life Information](#)

Take-back No

WEEE Label The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Technical Illustration

### Assembly's dimensions

---

