

Product datasheet

Specifications



iEM3000 energy meter. 63 A

A9MEM3100

Price: 5,195.27 ZAR

Main

Range	Acti9
range of product	Acti9 iEM3000
Product or component type	Energy meter
Device short name	iEM3100

Market segment

Buildings small building cost management: billing: main incomer
Buildings small building cost management: billing: sub feeder
Buildings small building cost management: billing: panelboard
Buildings medium building cost management: billing: main incomer
Buildings medium building cost management: billing: sub feeder
Buildings medium building cost management: billing: panelboard
Buildings large building cost management: billing: main incomer
Buildings large building cost management: billing: sub feeder
Buildings large building cost management: billing: panelboard
Buildings multi-site cost management: billing: main incomer
Buildings multi-site cost management: billing: sub feeder
Buildings multi-site cost management: billing: panelboard
Data center cost management: billing
Healthcare cost management: billing
Industry cost management: billing
Buildings small building cost management: cost allocation: main incomer
Buildings small building cost management: cost allocation: sub feeder
Buildings small building cost management: cost allocation: panelboard
Buildings medium building cost management: cost allocation: main incomer
Buildings medium building cost management: cost allocation: sub feeder
Buildings medium building cost management: cost allocation: panelboard
Buildings large building cost management: cost allocation: main incomer
Buildings large building cost management: cost allocation: sub feeder
Buildings large building cost management: cost allocation: panelboard
Buildings multi-site cost management: cost allocation: main incomer
Buildings multi-site cost management: cost allocation: sub feeder
Buildings multi-site cost management: cost allocation: panelboard
Data center cost management: cost allocation
Healthcare cost management: cost allocation
Industry cost management: cost allocation

Complementary

Poles description	1P + N 3P 3P + N
Type of measurement	Active energy
Device application	Partial meter Sub billing
Accuracy class	Class 1 active energy conforming to IEC 62053-21 Class 1 active energy conforming to IEC 61557-12
input type	Direct connection
[In] rated current	63 A
Rated voltage	100...277 V 173...480 V

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Network frequency	60 Hz 50 Hz
Technology type	Electronic
Display type	LCD display
Sampling rate	32 samples/cycle
Measurement current	0...63 A
Maximum value measured	99999999.9 kWh
Communication port protocol	-
Communication port support	-
Local signalling	Green indicator light: power ON Yellow flashing LED: accuracy checking
Number of inputs	0
Number of outputs	0
Mounting mode	Clip-on
Mounting support	DIN rail
Connections - terminals	Screw terminals 16 mm ² cable(s)
Overvoltage category	III
Standards	BS EN 61557-12:2021 IEC 61557-12:2021 EN 61557-12:2021 BS EN 61326-1 IEC 61326-1 EN 61326-1 BS EN 62052-11:2020 IEC 62052-11:2020 EN 62052-11:2020 BS EN 62053-21 IEC 62053-21 EN 62053-21 BS EN 62052-31:2015 IEC 62052-31:2015 EN 62052-31:2015 BS EN 61010-1:2010 EN 61010-1:2010 IEC 61010-1:2010 UL 61010-1:2010 BS EN 61010-2-30 IEC 61010-2-30 EN 61010-2-30 UL 61010-2-30 ANSI C12.16
Product certifications	CE conforming to IEC 61010-1 (safety) CE conforming to EN 61557-12 (power monitor) CE conforming to EN/IEC 61326-1 (EMC) UKCA conforming to BS EN 61010-1 (safety) UKCA conforming to BS EN 61557-12 (power monitor) UKCA conforming to BS EN 61326-1 (EMC) CULus conforming to UL 61010-1 (safety) CULus conforming to EN 61010-1 (safety) EAC (sub-meter) KZ conforming to NMI M 6-1 KZ NMI conforming to NMI M 6-1
Market segment	Residential Small commercial
Compatibility code	IEM3100

Environment

IP degree of protection	IP40 front panel: conforming to IEC 60529 IP20 body: conforming to IEC 60529
--------------------------------	---

Pollution degree	2
Relative humidity	5...95 % at 50 °C
Ambient air temperature for operation	-25...70 °C - IEC
Ambient air temperature for storage	-40...85 °C
Operating altitude	< 3000 m
Colour	White
9 mm pitches	10
Width	90 mm
Height	95 mm
Depth	69 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.500 cm
Package 1 Width	9.500 cm
Package 1 Length	10.200 cm
Package 1 Weight	418.700 g
Unit Type of Package 2	S03
Number of Units in Package 2	30
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	12.961 kg

Contractual warranty

Warranty (in months)	18
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint 56

Environmental Disclosure [Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number 6573da86-26ed-4686-b34d-5d3642e53d08

REACH Regulation [REACH Declaration](#)

Use Longer



Lifetime extension

Repair No

Use Again



Repack and remanufacture

End of life manual availability [End of Life Information](#)

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Technical Illustration

User interface / product ON

