

Product datasheet

Specifications



switch Acti9 iSW - 2 poles - 32 A - 415V

A9S60232

Price: 363.05 ZAR

Main

| | |
|---------------------------|---------------------|
| Range | Acti9 |
| Product name | Acti9 iSW |
| Product or component type | Switch disconnecter |
| Device short name | iSW |
| Device application | Control |
| Poles description | 2P |
| Utilisation category | AC-22A |
| Suitability for isolation | Yes |

Complementary

| | |
|--|---|
| [Ie] rated operational current | 32 A at 415 V AC 50/60 Hz |
| [Ue] rated operational voltage | 415 V AC 50/60 Hz |
| [Ui] rated insulation voltage | 500 V AC 50/60 Hz conforming to EN/IEC 60669-2-4 |
| [Uimp] rated impulse withstand voltage | 4 kV |
| control type | Toggle |
| Local signalling | ON/OFF indication |
| Contact position indicator | Yes |
| Mounting mode | Fixed |
| Mounting support | DIN rail |
| 9 mm pitches | 2 |
| Height | 77 mm |
| Width | 18 mm |
| Depth | 70 mm |
| Colour | White |
| Mechanical durability | 300000 cycles |
| Electrical durability | 30000 cycles |
| Connections - terminals | Tunnel type terminals - 10 mm ² - rigid Tunnel type terminals - 10 mm ² - flexible Tunnel type terminals - 10 mm ² - flexible with ferrule |
| Wire stripping length | 9 mm |
| tightening torque | 1.2 N.m |

Environment

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

| | |
|---------------------------------------|------------------|
| Standards | EN/IEC 60669-2-4 |
| IP degree of protection | IP4 |
| Pollution degree | 2 |
| Tropicalisation | 2 |
| Relative humidity | 95 % at 55 °C |
| Ambient air temperature for operation | -20...50 °C |
| Ambient air temperature for storage | -40...70 °C |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 7.800 cm |
| Package 1 Width | 1.800 cm |
| Package 1 Length | 8.500 cm |
| Package 1 Weight | 65.000 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 12 |
| Package 2 Height | 8.800 cm |
| Package 2 Width | 9.500 cm |
| Package 2 Length | 22.200 cm |
| Package 2 Weight | 832.000 g |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 144 |
| Package 3 Height | 30.000 cm |
| Package 3 Width | 30.000 cm |
| Package 3 Length | 40.000 cm |
| Package 3 Weight | 10.410 kg |

Contractual warranty

| | |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint 3

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic Yes

[EU RoHS Directive](#) Compliant

SCIP Number 58250416-ad9e-49ce-8d91-cdef0ea3a401

REACH Regulation [REACH Declaration](#)

Halogen-free status Product contains halogen above thresholds

Use Longer

Lifetime extension

Repair No

Use Again

Repack and remanufacture

End of life manual availability [End of Life Information](#)

Take-back No

WEEE Label The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins