

Product datasheet

Specifications



APC Smart-UPS On-Line, 3kVA,
Rackmount 2U, 230V, 6x C13+2x
C19 IEC outlets, SmartSlot,
Extended runtime, W/rail kit, W/O
Lithium-ion external battery

SRT3000UXI-LI

Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead time	Usually in Stock

Main

Main Input Voltage	230 V AC 1 phase
Input voltage	220 V 240 V
Input Connection Type	BS1363A British IEC 60320 C20 Schuko CEE 7 / EU1-16P
Input voltage limits	50...150 V 40% load 80...150 V
Network frequency	40...70 Hz auto-sensing
Output voltage	230 V 1 phase
Output voltage	220 V 240 V
Rated power in W	2700 W
rated power in VA	3000 VA
Output connection type	6 IEC 60320 C13 2 IEC 60320 C19
Bypass type	Built-in bypass
Crest factor	3 : 1
Harmonic distortion	Less than 2 %
Maximum configurable power in VA	3000 VA
Maximum configurable power in W	2700 W
UPS type	Double conversion online
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

Complementary

Battery type	Li-Ion (Lithium-Ion)
Extended runtime	1
Number of battery filled slots	0
Number of battery free slots	0

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Battery type	Li-Ion (Lithium-Ion) internal included
Emergency power off	Yes
Free slots	1
Alarm	Audible and visible alarms : prioritized by severity
UPS connectivity	Serial port USB port
Surge energy rate	432 J
Number of rack unit	2U
Cable length	1.8 m
Number of cables	1
Colour	Black
Height	432 mm
Width	85 mm
Depth	508 mm
Net weight	22 kg
Mounting preference	No preference
Mounting mode	Rack-mounted with kit
Two post mountable	0
USB compatible	Yes
Mounting position	Vertical
Mounting mode	Rack-mounted with included kit
Provided equipment	CD with software Communication cable Documentation CD Installation guide Removable support feet USB cable Warranty card
Number of power module filled slots	0
Number of power module free slots	0
Additional specification	High density
Redundant	No
Range of product	Smart-UPS On-Line
Product or component type	Uninterruptible power supply (UPS)
Number of tare power	15 W
Curve equation	Efficiency
Curve load maximum	100 %
Curve X-axis maximum	100 %
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency

Curve Y-axis units	Percentage
Graph display	1
Show note OP temperature	No
Battery curve	D
Liquid value	0
UPS design life	7 year(s)
Battery power in VAH	0 VAh runtime
UPS size	S

Environment

Product certifications	CE EAC UK PSTI
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-20...50 °C
Storage altitude	0...15240 m
IP degree of protection	IP20
Relative humidity	0...95 % non-condensing
Storage Relative Humidity	0...95 % non-condensing
Acoustic level	50 dBA
Heat dissipation	317 Btu/h
Operating altitude	0...10000 ft

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.6 cm
Package 1 Width	74.9 cm
Package 1 Length	59.4 cm
Package 1 Weight	29.6 kg

Contractual warranty

Warranty (in months)	60
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint 7631

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number 0637234b-27c7-4e32-ae29-543dd4803a99

REACH Regulation [REACH Declaration](#)

Use Longer

Lifetime extension

Repair No

Use Again

Repack and remanufacture

End of life manual availability [End of Life Information](#)

Removable battery User replaceable

Take-back No

WEEE Label The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins