

Product datasheet

Specifications



iEM3265 energy meter - CT - BACnet - 1 digital I - 1 digital O - multi-tariff - MID

A9MEM3265

⚠ Discontinued on: 01 Dec 2024

⚠ To be discontinued

Price: 7,052.79 ZAR

Main

Range	Acti9
range of product	Acti9 iEM3000
Product or component type	Energy meter
Device short name	iEM3265

Market segment	Buildings small building cost management: billing: main incomer Buildings small building cost management: billing: sub feeder Buildings small building cost management: billing: panelboard Buildings medium building cost management: billing: main incomer Buildings medium building cost management: billing: sub feeder Buildings medium building cost management: billing: panelboard Buildings large building cost management: billing: main incomer Buildings large building cost management: billing: sub feeder Buildings large building cost management: billing: panelboard Buildings multi-site cost management: billing: main incomer Buildings multi-site cost management: billing: sub feeder Buildings multi-site cost management: billing: panelboard Data center cost management: billing Healthcare cost management: billing Industry cost management: billing Buildings small building cost management: cost allocation: main incomer Buildings small building cost management: cost allocation: sub feeder Buildings small building cost management: cost allocation: panelboard Buildings medium building cost management: cost allocation: main incomer Buildings medium building cost management: cost allocation: sub feeder Buildings medium building cost management: cost allocation: panelboard Buildings large building cost management: cost allocation: main incomer Buildings large building cost management: cost allocation: sub feeder Buildings large building cost management: cost allocation: panelboard Buildings multi-site cost management: cost allocation: main incomer Buildings multi-site cost management: cost allocation: sub feeder Buildings multi-site cost management: cost allocation: panelboard Data center cost management: cost allocation Healthcare cost management: cost allocation Industry cost management: cost allocation
----------------	--

Complementary

Poles description	3P 1P + N 3P + N
Type of measurement	Active and reactive energy Active and reactive power Current Voltage
Metering type	Active, reactive, apparent energy (signed, four quadrant)
Device application	Sub billing Partial meter Multi-tariff

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Accuracy class	Class 0.5S active energy conforming to IEC 62053-22 Class 0.5S active energy conforming to IEC 61557-12 Class C active energy conforming to EN 50470-3
input type	Current transformer 1 A or 5 A
[In] rated current	5 A 1 A
Rated voltage	100...277 V 173...480 V
Network frequency	60 Hz 50 Hz
Technology type	Electronic
Display type	LCD display
Sampling rate	32 samples/cycle
Measurement current	1...32767000 mA
Maximum value measured	99999999 MWh
tariff input	Tariff (4)
Communication port protocol	BACnet at 9.6, 19.2, 38.4, 57.6, 76.8 kbauds, insulation 4000 V
Communication port support	Screw terminal block: RS485
Local signalling	Green indicator light: power ON Yellow flashing LED: accuracy checking alarm: overload
Number of inputs	1 digital 0...5 V/11...40 V 24 V DC
Number of outputs	1 digital (static)
Output voltage	5...40 V DC@50 mA
Mounting mode	Clip-on
Mounting support	DIN rail
Connections - terminals	Current circuit: screw terminals 6 mm ² cable(s) Voltage circuit: screw terminals 2.5 mm ² cable(s)
Overvoltage category	III

Standards	BS EN 61557-12:2021 IEC 61557-12:2021 EN 61557-12:2021 BS EN 61326-1 IEC 61326-1 EN 61326-1 BS EN 62052-11:2020 IEC 62052-11:2020 EN 62052-11:2020 BS EN 62053-21 IEC 62053-21 EN 62053-21 BS EN 62052-22 IEC 62053-22:2020 EN 62052-22 BS EN 62052-23 IEC 62053-23:2020 EN 62052-23 BS EN 62052-31:2015 IEC 62052-31:2015 EN 62052-31:2015 BS EN 61010-1:2010 EN 61010-1:2010 IEC 61010-1:2010 UL 61010-1:2010 BS EN 61010-2-30 IEC 61010-2-30 EN 61010-2-30 UL 61010-2-30 BS EN 50470-3 EN 50470-3 BS EN 50470-1 EN 50470-1 ANSI C12.20
------------------	--

Product certifications	CE conforming to IEC 61010-1 (safety) CE conforming to EN 61557-12 (power monitor) CE conforming to EN/IEC 61326-1 (EMC) UKCA conforming to BS EN 61010-1 (safety) UKCA conforming to BS EN 61557-12 (power monitor) UKCA conforming to BS EN 61326-1 (EMC) CULus conforming to UL 61010-1 (safety) CULus conforming to EN 61010-1 (safety) EAC conforming to EN 50470-3 (sub-meter) RCM conforming to EN 62052 (sub-meter) KZ conforming to EN 50470-3 (sub-meter) METAS conforming to EN 50470-1 (sub-meter) MID conforming to EN 50470-3 (sub-meter) MID conforming to EN 50470-1 (sub-meter) NMI conforming to NMI M 6-1
-------------------------------	--

Compatibility code	IEM3265
---------------------------	---------

Environment

IP degree of protection	IP40 front panel: conforming to IEC 60529 IP20 body: conforming to IEC 60529
Pollution degree	2
Relative humidity	5...95 % at 50 °C
Ambient air temperature for operation	-25...70 °C - IEC
Ambient air temperature for storage	-40...85 °C
Operating altitude	< 3000 m
Colour	White
9 mm pitches	10
Width	90 mm
Height	95 mm
Depth	69 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.800 cm
Package 1 Width	9.400 cm
Package 1 Length	10.500 cm
Package 1 Weight	368.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	30
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	11.366 kg
Unit Type of Package 3	P12
Number of Units in Package 3	720
Package 3 Height	110.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	281.784 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint 60

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number 892306d0-669d-4f6c-bc56-a04ad95994e5

REACH Regulation [REACH Declaration](#)

Use Longer

Lifetime extension

Repair No

Use Again

Repack and remanufacture

End of life manual availability [End of Life Information](#)

Take-back No

WEEE Label The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Technical Illustration

User interface / product ON

