

# Product datasheet

Specifications



APC Smart-UPS On-Line,  
2200VA, Lithium-ion, Rackmount  
4U, 230V, 6x C13+2x C19 IEC  
outlets, SmartSlot, Extended long  
runtime, Rail kit included

SRTL2200RM4UXLI

**Price: 94,760.00 ZAR**

## Overview

|              |   |
|--------------|---|
| Presentation | High density, double-conversion on-line power protection with long runtime. |
| Lead time    | Usually in Stock  |

## Main

|                                  |                                 |
|----------------------------------|---------------------------------|
| Main Input Voltage               | 230 V AC 1 phase                |
| Input voltage                    | 220 V                           |
| Input Connection Type            | IEC 60320 C20                   |
| Input voltage limits             | 160...275 V                     |
| Network frequency                | 40...70 Hz auto-sensing         |
| Output voltage                   | 230 V AC 1 phase                |
| Output voltage                   | 220 V                           |
| Rated power in W                 | 1980 W                          |
| rated power in VA                | 2200 VA                         |
| Output connection type           | 6 IEC 60320 C13                 |
| Bypass type                      | Built-in bypass                 |
| Crest factor                     | 3 : 1                           |
| Harmonic distortion              | Less than 2 %                   |
| Maximum configurable power in VA | 2200 VA                         |
| Maximum configurable power in W  | 1980 W                          |
| UPS type                         | Double conversion online        |
| Wave type                        | Sine wave                       |
| Output frequency                 | 50/60 Hz +/- 3 Hz sync to mains |

## Complementary

|                                |                      |
|--------------------------------|----------------------|
| Battery type                   | Li-Ion (Lithium-Ion) |
| Battery voltage                | 48 V                 |
| Extended runtime               | 1                    |
| Number of battery filled slots | 0                    |
| Number of battery free slots   | 0                    |
| Battery life                   | 5...10 year(s)       |

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

|  |  |
|--|--|
| <b>Battery charger power</b>               | 158 W rated  |
| <b>Battery type</b>                        | Li-Ion (Lithium-Ion) internal included               |
| <b>Emergency power off</b>                 | Yes  |
| <b>Free slots</b>                          | 1  |
| <b>Alarm</b>                               | Audible and visible alarms : prioritized by severity |
| <b>UPS connectivity</b>                    | Serial port<br>USB port                              |
| <b>Surge energy rate</b>                   | 432 J  |
| <b>Number of rack unit</b>                 | 4U   |
| <b>Cable length</b>                        | 1.8 m  |
| <b>Number of cables</b>                    | 1  |
| <b>Colour</b>                              | Black with silver front bezel                        |
| <b>Height</b>                              | 171 mm   |
| <b>Width</b>                               | 432 mm   |
| <b>Depth</b>                               | 639 mm   |
| <b>Net weight</b>                          | 43.2 kg  |
| <b>Mounting preference</b>                 | No preference  |
| <b>Mounting mode</b>                       | Rack-mounted with kit                                |
| <b>Two post mountable</b>                  | 0  |
| <b>USB compatible</b>                      | Yes  |
| <b>Mounting position</b>                   | Horizontal<br>Vertical                               |
| <b>Mounting mode</b>                       | Rack-mounted with included kit                       |
| <b>Number of power module filled slots</b> | 0  |
| <b>Number of power module free slots</b>   | 0  |
| <b>Additional specification</b>            | Lithium-Ion  |
| <b>Redundant</b>                           | No   |
| <b>Range of product</b>                    | Smart-UPS On-Line                                    |
| <b>Product or component type</b>           | Uninterruptible power supply (UPS)                   |

## Environment

|  |                         |
|--|-------------------------|
| <b>Product certifications</b>                | CE<br>UK PSTI           |
| <b>Marking</b>                               | CE Mark                 |
| <b>Ambient air temperature for operation</b> | 0...40 °C               |
| <b>Ambient air temperature for storage</b>   | -20...50 °C             |
| <b>Storage altitude</b>                      | 0...15240 m             |
| <b>IP degree of protection</b>               | IP20                    |
| <b>Relative humidity</b>                     | 0...95 % non-condensing |
| <b>Storage Relative Humidity</b>             | 0...95 % non-condensing |
| <b>Acoustic level</b>                        | 50 dBA                  |
| <b>Heat dissipation</b>                      | 317 Btu/h               |

---

|                    |              |
|--------------------|--------------|
| Operating altitude | 0...10000 ft |
|--------------------|--------------|

## Packing Units

---

|                        |     |
|------------------------|-----|
| Unit Type of Package 1 | PCE |
|------------------------|-----|

---

|                              |   |
|------------------------------|---|
| Number of Units in Package 1 | 1 |
|------------------------------|---|

---

|                  |         |
|------------------|---------|
| Package 1 Height | 24.5 cm |
|------------------|---------|

---

|                 |       |
|-----------------|-------|
| Package 1 Width | 60 cm |
|-----------------|-------|

---

|                  |       |
|------------------|-------|
| Package 1 Length | 81 cm |
|------------------|-------|

---

|                  |         |
|------------------|---------|
| Package 1 Weight | 56.5 kg |
|------------------|---------|

## Contractual warranty

---

|                      |    |
|----------------------|----|
| Warranty (in months) | 60 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better



### Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant with Exemptions

REACH Regulation

[REACH Declaration](#)

## Use Longer



### Lifetime extension

Repair

No

## Use Again



### Repack and remanufacture

End of life manual availability

[End of Life Information](#)

Removable battery

User replaceable

Take-back

No

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

---







