

Product datasheet

Specifications



APC Smart-UPS, Line Interactive,
500VA, Lithium-ion, Rackmount
1U, 230V, 4x IEC C13 outlets,
Network Card, Short Depth

SCL500RMI1UNC

Price: 16,541.60 ZAR

Overview

Presentation	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Lead time	Usually in Stock

Main

Main Input Voltage	230 V AC 1 phase
Input Connection Type	IEC 60320 C14
Input protection type	Circuit breaker
Input voltage limits	208...253 V
Network frequency	50/60 Hz +/- 3 Hz auto sensing
Output voltage	230 V AC 1 phase
Rated power in W	400 W
rated power in VA	500 VA
Output connection type	4 IEC 60320 C13
Harmonic distortion	Less than 5 %
Maximum configurable power in VA	500 VA
Maximum configurable power in W	400 W
Transfer time	6 ms typical : 10 ms maximum
UPS type	Line interactive
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

Complementary

Battery type	Li-Ion (Lithium-Ion)
Battery graph comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several v
Extended runtime	0
Battery design life	8...10 year(s)
Battery charger power	10 W rated
Battery type	Li-Ion (Lithium-Ion) internal included

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Control panel	LED status display with on line : on battery : replace battery and building wiring fault
Free slots	0
Preinstalled device	Network management card 3
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
UPS connectivity	Serial port USB port Embedded network management card 3
Surge energy rate	510 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449
Number of rack unit	1U
Colour	Black with silver front bezel
Height	44 mm
Width	432 mm
Depth	232 mm
Net weight	4.1 kg
Mounting preference	No preference
Mounting mode	Rack-mounted
USB compatible	Yes
Mounting mode	Rack-mounted
Provided equipment	Installation guide Rack mounting support rails USB cable
Redundant	No
Range of product	Smart-UPS
Product or component type	Uninterruptible power supply (UPS)
Number of tare power	10 W
Value multiplier	1
Curve equation	Efficiency
Curve fixed loss	0.0101
Curve load maximum	100 %
Curve load minimum	2 %
Curve proportional loss	0
Curve square loss	0.0015
Curve test cond ID	Curve fit of data measured in accordance with the ENERGY STAR Test Method for Uninterruptible Power Supplies. All measurements taken in normal mode(s), at typical environmental conditions, with 230V/50Hz electrical input and balanced resistive load (PF = 1.0) output.
Curve X-axis maximum	100 %
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %

Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Show note OP temperature	No
Battery curve	L1
Liquid value	0
Battery power in VAH	36 VAh runtime
UPS size	S

Environment

Product certifications	C-Tick CE EAC UK PSTI
Equipment protection policy	Lifetime : \$150000
Standards	EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0...7620 m
IP degree of protection	IP20
Relative humidity	0...95 % non-condensing
Storage Relative Humidity	0...95 % non-condensing
Acoustic level	45 dBA
Heat dissipation	41.61 Btu/h
Operating altitude	0...10000 ft

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	16.8 cm
Package 1 Width	59 cm
Package 1 Length	33.7 cm
Package 1 Weight	6.49 kg

Contractual warranty

Warranty (in months)	60
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint 180

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number 8519b6fb-f7a9-44f8-be44-5dee68362126

REACH Regulation [REACH Declaration](#)

Energy efficiency

Energy Efficiency Optimized Energy efficient product

Product contributes to saved and avoided emissions Yes

Use Longer

Lifetime extension

Repair No

Use Again

Repack and remanufacture

End of life manual availability [End of Life Information](#)

Removable battery User replaceable

Take-back No

WEEE Label The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

