

# Product datasheet

Specifications



## switch-disconnector iSW-NA - 1P + N - 40 A

A9S70640

⚠ Discontinued on: 01 Dec 2024

⚠ To be discontinued

### Main

Range	Acti9
Product name	Acti9 iSW-NA
Product or component type	Switch disconnecter
Device short name	iSW-NA
Device application	Isolation Control
Poles description	1P + N
Neutral position	Left
Utilisation category	AC-22A conforming to EN/IEC 60947-3
Suitability for isolation	Yes conforming to EN/IEC 60947-3

### Complementary

[Ie] rated operational current	40 A at 230/240 V AC 50/60 Hz
[Ue] rated operational voltage	230/240 V AC 50/60 Hz
[Icm] rated short-circuit making capacity	5 kA switch-disconnector alone
[Icw] rated short-time withstand current	800 A during 1 s
[Ui] rated insulation voltage	500 V AC 50/60 Hz conforming to EN/IEC 60947-3
[Uimp] rated impulse withstand voltage	6 kV conforming to EN/IEC 60947-3
control type	Toggle Remote tripping
Local signalling	ON/OFF indication
Contact position indicator	Yes
Mounting mode	Clip-on
Mounting support	DIN rail
Comb busbar and distribution block compatibility	Top or bottom: YES
9 mm pitches	4
Height	85 mm
Width	36 mm
Depth	74 mm
Net weight	0.17 kg
Colour	White

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

<b>Mechanical durability</b>	20000 cycles
<b>Electrical durability</b>	15000 cycles
<b>Connections - terminals</b>	Tunnel type terminals (top or bottom) 1 cable(s) 1...25 mm <sup>2</sup> flexible with cable end Tunnel type terminals (top or bottom) 1 cable(s) 1...25 mm <sup>2</sup> flexible without cable end Tunnel type terminals (top or bottom) 1 cable(s) 1...35 mm <sup>2</sup> rigid without cable end
<b>Wire stripping length</b>	14 mm
<b>tightening torque</b>	3.5 N.m
<b>Product compatibility</b>	Tripping release

## Environment

<b>Standards</b>	IEC 60947-3 EN 60947-3
<b>IP degree of protection</b>	IP20
<b>Pollution degree</b>	3 conforming to IEC 60947-3
<b>Tropicalisation</b>	2
<b>Relative humidity</b>	95 % at 55 °C
<b>Ambient air temperature for operation</b>	-35...70 °C
<b>Ambient air temperature for storage</b>	-40...85 °C

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	4.0 cm
<b>Package 1 Width</b>	8.0 cm
<b>Package 1 Length</b>	10.0 cm
<b>Package 1 Weight</b>	187.0 g
<b>Unit Type of Package 2</b>	S03
<b>Number of Units in Package 2</b>	54
<b>Package 2 Height</b>	30 cm
<b>Package 2 Width</b>	30 cm
<b>Package 2 Length</b>	40 cm
<b>Package 2 Weight</b>	10.468 kg

## Contractual warranty

<b>Warranty (in months)</b>	18
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Total lifecycle Carbon footprint 2

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic Yes

[EU RoHS Directive](#) Compliant

SCIP Number E5f22bd9-8e0c-4771-b932-618a392a4c8b

REACH Regulation [REACH Declaration](#)

Halogen-free status Halogen free plastic parts product

## Use Longer

### Lifetime extension

Repair No

## Use Again

### Repack and remanufacture

End of life manual availability No need of specific recycling operations

Take-back No

WEEE Label The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins