

# Product datasheet

Specifications



APC Smart-UPS Ultra On-Line, 2200VA, Lithium-ion, Rack/Tower 1U, 230V, 3x C13, 2x C19 IEC outlets, SmartConnect, Extended runtime, W/rail kit

SRTL2K2RM1UIC

⚠ To be discontinued

⚠ Discontinued on: 01 Dec 2024

**Price: 68,080.00 ZAR**

## Overview

Lead time Usually in Stock

## Main

Main Input Voltage	230 V AC 1 phase
Input voltage	230 V
Input Connection Type	BS1363A British IEC 320 C19/C21 Schuko CEE 7 / EU1-16P
Input voltage limits	160...275 V adjustable 220...240 V AC
Number of input connectors	1
Network frequency	50/60 Hz auto-sensing
Output voltage	230 V AC 1 phase
Output voltage	230 V
Rated power in W	2200 W
rated power in VA	2200 VA
Output connection type	3 IEC 320 C13 2 IEC 320 C19
Output connector type	IEC C13 3-wire
Bypass type	Internal bypass (automatic and manual)
Crest factor	3 : 1
Maximum configurable power in VA	2200 VA
Maximum configurable power in W	2200 W
Output harmonic distortion	< 2% at 100% linear load and < 5% at 100% non-linear load
UPS type	Double conversion online
Wave type	Sine wave
Efficiency	97 %
Output frequency	50/60 Hz +/- 3 Hz sync to mains

## Complementary

Battery type Li-Ion (Lithium-Ion)

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

<b>Battery voltage</b>	50 V
<b>Extended runtime</b>	1
<b>Battery recharge time</b>	1.5 h
<b>Number of battery replacement quantity</b>	1
<b>Battery design life</b>	8...10 year(s)
<b>Battery life</b>	8...10 year(s)
<b>Battery charger power</b>	448 W rated
<b>Battery type</b>	Li-Ion (Lithium-Ion) internal included
<b>Control panel</b>	Touch screen LCD user interface
<b>Emergency power off</b>	Yes
<b>Alarm</b>	Audible and visible alarms : prioritized by severity
<b>UPS connectivity</b>	Serial port USB port SmartConnect port
<b>Surge energy rate</b>	1600 J
<b>Number of rack unit</b>	1U
<b>Cable length</b>	2.4 m
<b>Number of cables</b>	1
<b>Colour</b>	Silver grey
<b>Height</b>	43 mm
<b>Width</b>	432 mm
<b>Depth</b>	560 mm
<b>Net weight</b>	15.9 kg
<b>Mounting preference</b>	No preference
<b>Mounting mode</b>	Rack-mounted with kit
<b>Two post mountable</b>	1
<b>USB compatible</b>	Yes
<b>Mounting position</b>	Horizontal Vertical
<b>Mounting mode</b>	Rack-mounted with included kit
<b>Provided equipment</b>	RJ45 cable Rack mounting brackets Network cable Terminal Stabilization feet Safety guide Rail extension Washer USB cable Screws
<b>Additional specification</b>	High density
<b>Redundant</b>	No
<b>Range of product</b>	Smart-UPS Ultra
<b>Product or component type</b>	Uninterruptible power supply (UPS)

## Environment

<b>Product certifications</b>	CE EAC RCM VDE UKCA UK PSTI
<b>Marking</b>	CE Mark
<b>Standards</b>	EN/IEC 62040-1 FCC CFR 47 part 15 class A IEC 62040-2 EN/IEC 61000-4-8 EN/IEC 61000-4-6 level 3 EN/IEC 61000-4-5 level 3 EN/IEC 61000-4-4 level 4
<b>Ambient air temperature for operation</b>	0...40 °C
<b>Ambient air temperature for storage</b>	-15...45 °C
<b>Storage altitude</b>	0...15240 m
<b>IP degree of protection</b>	IP20
<b>Relative humidity</b>	0...95 % non-condensing
<b>Storage Relative Humidity</b>	0...95 % non-condensing
<b>Acoustic level</b>	55 dB
<b>Heat dissipation</b>	325 Btu/h
<b>Operating altitude</b>	0...10000 ft

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	27.82 cm
<b>Package 1 Width</b>	56.4 cm
<b>Package 1 Length</b>	76.4 cm
<b>Package 1 Weight</b>	24.18 kg

## Contractual warranty

<b>Warranty (in months)</b>	60
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint 6410

Environmental Disclosure [Product Environmental Profile](#)

## Use Better



### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number 5ee38369-4dfb-4636-ab65-b08aa3242891

REACH Regulation [REACH Declaration](#)

## Use Longer



### Lifetime extension

Repair No

## Use Again



### Repack and remanufacture

End of life manual availability [End of Life Information](#)

Removable battery User replaceable

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

---







