

# Product datasheet

Specifications



## Miniature circuit-breaker. Acti9 C120N. 4P. 80 A. C curve. 10 kA (IEC 60947-2)

A9N60741

**Price: 5,520.84 ZAR**

### Main

Range	Acti9
Product name	Acti9 C120
Product or component type	Miniature circuit-breaker
Device short name	C120N
Device application	Distribution
Poles description	4P
Number of protected poles	4
[In] rated current	80 A at 40 °C
Network type	AC
Trip unit technology	Thermal-magnetic
Curve code	C
Breaking capacity	10 kA Icu at <= 500 V DC conforming to EN/IEC 60947-2 10 kA Icu at 230...400 V AC 50/60 Hz conforming to EN/IEC 60947-2
Standards	EN/IEC 60947-2

### Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	<= 500 V DC 230...400 V AC 50/60 Hz
Magnetic tripping limit	8 x In +/- 20 %
[Ics] rated service breaking capacity	7.5 kA 75 % conforming to EN/IEC 60947-2 - 230...400 V AC 50/60 Hz
Limitation class	3 conforming to EN/IEC 60947-2
[Ui] rated insulation voltage	500 V AC 50/60 Hz conforming to EN/IEC 60947-2
[Uimp] rated impulse withstand voltage	6 kV conforming to EN/IEC 60947-2
control type	Toggle
Local signalling	ON/OFF indication
Mounting mode	Clip-on
Mounting support	35 mm symmetrical DIN rail
Comb busbar and distribution block compatibility	YES
9 mm pitches	12
Height	81 mm
Depth	73 mm

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

<b>Width</b>	108 mm
<b>Net weight</b>	0.82 kg
<b>Colour</b>	White
<b>Mechanical durability</b>	20000 cycles
<b>Electrical durability</b>	5000 cycles
<b>Locking options description</b>	Handle sealable with cable diameter 0.7mm in OFF or ON position
<b>Connections - terminals</b>	Tunnel type terminals1...50 mm <sup>2</sup> rigid Tunnel type terminals1.5...35 mm <sup>2</sup> flexible
<b>Wire stripping length</b>	15 mm
<b>Tightening torque</b>	3.5 N.m
<b>Earth-leakage protection</b>	Separate block

## Environment

<b>IP degree of protection</b>	IP20 conforming to IEC 60529
<b>Pollution degree</b>	3 conforming to IEC 60947-2
<b>Overvoltage category</b>	III
<b>Tropicalisation</b>	2 conforming to IEC 60068-1
<b>Relative humidity</b>	95 % at 55 °C
<b>Ambient air temperature for operation</b>	-30...70 °C
<b>Ambient air temperature for storage</b>	-40...80 °C

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	8.700 cm
<b>Package 1 Width</b>	11.000 cm
<b>Package 1 Length</b>	9.300 cm
<b>Package 1 Weight</b>	773.000 g
<b>Unit Type of Package 2</b>	BB1
<b>Number of Units in Package 2</b>	3
<b>Package 2 Height</b>	8.700 cm
<b>Package 2 Width</b>	9.900 cm
<b>Package 2 Length</b>	33.900 cm
<b>Package 2 Weight</b>	2.508 kg
<b>Unit Type of Package 3</b>	S03
<b>Number of Units in Package 3</b>	18
<b>Package 3 Height</b>	30.000 cm
<b>Package 3 Width</b>	30.000 cm
<b>Package 3 Length</b>	40.000 cm
<b>Package 3 Weight</b>	15.535 kg

## Contractual warranty





## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Total lifecycle Carbon footprint 59

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic Yes

[EU RoHS Directive](#) Compliant

SCIP Number Ab76a2c8-39ad-4485-a07c-19f81f42d0a0

REACH Regulation [REACH Declaration](#)

Halogen-free status Product contains halogen above thresholds

## Use Longer

### Lifetime extension

Repair No

## Use Again

### Repack and remanufacture

End of life manual availability No need of specific recycling operations

Take-back No

WEEE Label The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins