

Product datasheet

Specifications



APC Smart-UPS SRT 5000VA RM 208/230V HW



SRT5KRMXLW-HW

Price: 93,840.00 ZAR

Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead time	Usually in Stock

Main

Main Input Voltage	208 V AC 1 phase 230 V AC 1 phase
Input voltage	220 V 240 V
Input voltage limits	100...275 V adjustable (half load)
Number of input connectors	1 hard wire 3-wire (2P + E) 1 hard wire 3-wire (1P + N + E)
Network frequency	40...70 Hz auto-sensing
Output voltage	208 V 1 phase 230 V 1 phase
Output voltage	220 V 240 V
Rated power in W	4500 W
rated power in VA	5000 VA
Output connector type	Hard wire 3-wire (H N + E) for 1 zone(s) Hard wire 3-wire (2P + E) for 1 zone(s)
Bypass type	Internal bypass (automatic and manual)
Crest factor	3 : 1
Harmonic distortion	Less than 2 %
Maximum configurable power in VA	5000 VA
Maximum configurable power in W	4500 W
UPS type	Double conversion online
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

Complementary

Battery type	Lead-acid battery
Battery voltage	192 V
Extended runtime	1
Number of battery filled slots	0
Battery recharge time	1.5 h

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Number of battery replacement quantity	1
Battery life	3...5 year(s)
Battery charger power	560 W rated
Battery type	Lead-acid internal included
Emergency power off	Yes
Free slots	1
Preinstalled device	Network management card 3 with environmental monitoring
Alarm	Audible and visible alarms : prioritized by severity
UPS connectivity	Serial port USB port Pre-installed network management card 3
Surge energy rate	480 J
Number of rack unit	3U
Colour	Black
Height	130 mm
Width	432 mm
Depth	719 mm
Net weight	55.79 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted
Two post mountable	0
USB compatible	Yes
Mounting position	Horizontal
Mounting mode	Rack-mounted with kit sold separately
Provided equipment	CD with software Documentation CD Installation guide Rack mounting hardware Rack mounting support rails Removable support feet Temperature probe User manual Warranty card Web/SNMP management card
Number of power module filled slots	0
Number of power module free slots	0
Additional specification	High density
Redundant	No
Range of product	Smart-UPS On-Line
Product or component type	Uninterruptible power supply (UPS)
Number of tare power	78 W
Curve equation	Efficiency
Curve fixed loss	0.0138
Curve load maximum	100 %

Curve load minimum	2 %
Curve proportional loss	0.024
Curve square loss	0.0219
Curve test cond ID	Curve fit of data measured in accordance with the ENERGY STAR Test Method for Uninterruptible Power Supplies. All measurements taken in normal mode(s), at typical environmental conditions, with 230V/50Hz electrical input and balanced resistive load (PF = 1.0) output.
Curve X-axis maximum	100 %
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Show note OP temperature	No
Battery curve	D
Liquid value	0
Battery design life	2 year(s)
UPS design life	7 year(s)
Battery power in VAH	845 VAh runtime
Battery option	SRT192RMBP 1 2535 VAh SRT192RMBP 2 4225 VAh SRT192RMBP 3 5915 VAh SRT192RMBP 4 7605 VAh SRT192RMBP 5 9295 VAh SRT192RMBP 6 10985 VAh SRT192RMBP 8 14365 VAh SRT192RMBP 10 17745 VAh
UPS size	S

Environment

Product certifications	CE EAC ENERGY STAR V2.0 (USA) FCC part 15 class A IRAM NOM RCM UL 1778 VDE
Marking	CE Mark
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0...15240 m
IP degree of protection	IP20

Relative humidity	0...95 % non-condensing
Storage Relative Humidity	0...95 % non-condensing
Acoustic level	55 dBA
Heat dissipation	931 Btu/h
Operating altitude	0...10000 ft

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	33 cm
Package 1 Width	96 cm
Package 1 Length	61 cm
Package 1 Weight	68.04 kg

Contractual warranty

Warranty (in months)	24 Battery 36 UPS
-----------------------------	-------------------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint 10863

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number 409c68a1-39a6-4e5f-b080-12befe783ad8

REACH Regulation [REACH Declaration](#)

Energy efficiency

ENERGY STAR® ENERGY STAR UPS V2.0 (USA)

Use Longer

Lifetime extension

Repair No

Use Again

Repack and remanufacture

End of life manual availability [End of Life Information](#)

Removable battery User replaceable

Take-back No

WEEE Label The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative











