

# Product datasheet

Specifications



## Circuit breaker ComPacT NSX400HB2. 100kA at 690VAC. MicroLogic 2.3 trip unit 250A. 3 poles 3d

C40W32D250

⚠ Discontinued on: 01 Dec 2024

⚠ To be discontinued

**Price: 22,402.96 ZAR**

### Main

|                                |   |
|--------------------------------|---|
| Range                          | ComPacT   |
| Product name                   | ComPacT NSX   |
| Device short name              | NSX400HB2   |
| Product or component type      | Circuit breaker   |
| Device application             | Distribution  |
| Poles description              | 3P  |
| Protected poles description    | 3D  |
| [In] rated current             | 250 A at 40 °C  |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz   |
| Network type                   | AC  |
| Network frequency              | 50/60 Hz  |
| Suitability for isolation      | Yes conforming to EN/IEC 60947-2  |
| Utilisation category           | Category A  |
| Breaking capacity              | 100 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>100 kA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2<br>100 kA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Breaking capacity code         | HB2 100 kA 690 V AC   |
| Trip unit name                 | MicroLogic 2.3  |
| Trip unit technology           | Electronic  |
| Trip unit protection functions | LSol  |
| Control type                   | Toggle  |
| Circuit breaker mounting mode  | Fixed   |

### Complementary

|  |   |
|--|---|
| [UI] rated insulation voltage          | 800 V AC 50/60 Hz   |
| [Uimp] rated impulse withstand voltage | 8 kV  |
| [Ics] rated service breaking capacity  | 100 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>100 kA at 525 V AC 50/60 Hz conforming to IEC 60947-2<br>100 kA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Mechanical durability                  | 15000 cycles  |

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

|  |  |
|--|--|
| <b>Electrical durability</b>                                     | 12000 cycles at 440 V In/2<br>6000 cycles at 440 V In<br>6000 cycles at 690 V In/2<br>3000 cycles at 690 V In  |
| <b>Power dissipation per pole</b>                                | 19.2 W   |
| <b>Mounting support</b>  | Backplate  |
| <b>Mounting position</b>   | Horizontal and vertical<br>Flat on the back  |
| <b>Upside connection</b>   | Front  |
| <b>Downside connection</b>                                       | Front  |
| <b>Connection pitch</b>  | 45 mm  |
| <b>Protection type</b>   | L : for overload protection (long time)<br>So : for short time short-circuit protection with fixed delay<br>I : for instantaneous short-circuit protection |
| <b>Trip unit rating</b>  | 250 A at 40 °C   |
| <b>Long-time pick-up adjustment type Ir (thermal protection)</b> | Adjustable 9 settings  |
| <b>[Ir] long-time protection pick-up adjustment range</b>        | 70...250 A   |
| <b>Long-time protection delay adjustment type tr</b>             | Fixed  |
| <b>[tr] long-time delay adjustment range</b>                     | 400 s at 1.5 x Ir<br>16 s at 6 x Ir<br>11 s at 7.2 x Ir  |
| <b>Thermal memory</b>  | 20 minutes before and after tripping   |
| <b>Short-time protection pick-up adjustment type Isd</b>         | Adjustable 9 settings  |
| <b>[Isd] Short-time protection pick-up adjustment range</b>      | 1.5...10 x Ir  |
| <b>Short-time protection delay adjustment type tsd</b>           | Fixed  |
| <b>Instantaneous protection pick-up adjustment type Ii</b>       | Fixed  |
| <b>[Ii] instantaneous protection pick-up adjustment range</b>    | 3000 A   |
| <b>Earth-leakage protection</b>                                  | Without  |
| <b>Zone selective interlocking ZSI</b>                           | Without  |
| <b>Number of slots</b>   | 6 slot(s)  |
| <b>Local signalling</b>  | Flashing LED (green) for ready to operate<br>LED 105 % Ir (red) for overload<br>LED 90 % Ir (orange) for overload  |
| <b>Width (W)</b>   | 140 mm   |
| <b>Height (H)</b>  | 255 mm   |
| <b>Depth (D)</b>   | 110 mm   |
| <b>Net weight</b>  | 6.05 kg  |

## Environment

|  |                              |
|--|------------------------------|
| <b>Standards</b>                         | EN/IEC 60947-2               |
| <b>Overvoltage category</b>              | III                          |
| <b>Electrical shock protection class</b> | Class II on front face       |
| <b>Pollution degree</b>                  | 3 conforming to IEC 60664-1  |
| <b>IP degree of protection</b>           | IP40 conforming to IEC 60529 |
| <b>IK degree of protection</b>           | IK07 conforming to IEC 62262 |

|  |  |
|--|--|
| <b>Ambient air temperature for operation</b> | -25...70 °C  |
| <b>Ambient air temperature for storage</b>   | -50...85 °C  |
| <b>Relative humidity</b>                     | 0...95 %   |
| <b>Operating altitude</b>                    | 0...2000 m without derating<br>2000 m...5000 m with derating |

## Packing Units

|                                     |            |
|-------------------------------------|------------|
| <b>Unit Type of Package 1</b>       | PCE        |
| <b>Number of Units in Package 1</b> | 1          |
| <b>Package 1 Height</b>             | 15.200 cm  |
| <b>Package 1 Width</b>              | 15.200 cm  |
| <b>Package 1 Length</b>             | 29.200 cm  |
| <b>Package 1 Weight</b>             | 5.420 kg   |
| <b>Unit Type of Package 2</b>       | S04        |
| <b>Number of Units in Package 2</b> | 3          |
| <b>Package 2 Height</b>             | 30 cm      |
| <b>Package 2 Width</b>              | 40 cm      |
| <b>Package 2 Length</b>             | 60 cm      |
| <b>Package 2 Weight</b>             | 16.910 kg  |
| <b>Unit Type of Package 3</b>       | P12        |
| <b>Number of Units in Package 3</b> | 12         |
| <b>Package 3 Height</b>             | 45.000 cm  |
| <b>Package 3 Width</b>              | 80.000 cm  |
| <b>Package 3 Length</b>             | 120.000 cm |
| <b>Package 3 Weight</b>             | 79.640 kg  |

## Contractual warranty

|                             |    |
|-----------------------------|----|
| <b>Warranty (in months)</b> | 18 |
|-----------------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Total lifecycle Carbon footprint 167

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic Yes

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number 25ca3248-85d0-423a-a9d8-5b7aeb52e7b6

REACH Regulation [REACH Declaration](#)

Halogen-free status Product contains halogen above thresholds

PVC free Yes

Silicone-free No

## Use Longer

### Lifetime extension

Repair No

Updatability No

## Use Again

### Repack and remanufacture

End of life manual availability [End of Life Information](#)

Take-back No

WEEE Label The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Offer Marketing Illustration

Product benefits / Features

---



**ComPacT NSX**  
Range Accessories

Wireless auxiliary contact

Short terminal shield

Interphase barriers

Long terminal shield

Rotary handles

Standard auxiliary contact

MN undervoltage release

MX shunt release

Standard motor mechanism module

The illustration displays a collection of accessories for the ComPacT NSX circuit breaker range. At the top left, a large image shows a circuit breaker with a green arc behind it. Below this, nine individual accessories are arranged in a 3x3 grid, each with a small image and a text label. The accessories include: a wireless auxiliary contact (green and black), a short terminal shield (black), interphase barriers (black), a long terminal shield (black), rotary handles (black and green), a standard auxiliary contact (grey), an MN undervoltage release (black), an MX shunt release (yellow and black), and a standard motor mechanism module (black).

Offer Marketing Illustration

Product benefits / Features

---



Offer Marketing Illustration

Product benefits / Features

---

## ComPacT NSX Moulded Case Circuit Breaker



### Protection begins with prevention

Designed to prevent an electrical fire through integrated earth leakage protection with preventive maintenance thanks to its Everlink power connections.



### Maximize power availability

By providing corrective, preventive, and predictive maintenance for asset management thanks to our advanced MicroLogic trip units.



### Connectivity

Designed to connect to EcoStruxure Power, an IoT-connected architecture for improving every aspect of your power distribution system.



Offer Marketing Illustration

Product benefits / Features

---



**ComPacT NSX**  
Technical Benefits

- Nominal current: 16 to 630 A and 9 breaking capacities for the 2 sizes of circuit breakers
- 1, 2, 3, and 4 pole versions available
- Large range of electronic and thermal-magnetic protections
- Plug and ready wiring system and communicating accessories
- Integrated earth leakage protection via MicroLogic Vigi (earth leakage circuit breaker - ELCB)
- Advanced trip unit with integrated power metering: I, U, P, E, THD, f, CosPhi